



SAFETY JOGGER

INDUSTRIAL



ALLFLEX 12PACK 4131A

ALLFLEX12P

Precision Gloves For Delicate Handling 12PACK

ALLFLEX gloves combine agility and comfort for delicate work. Nitrile coating ensures grip and control, while the nylon spandex liner boosts flexibility.

Performance level	4131A
Liner	15 Gauge/Polyamide/Spandex
Coating	Foam Nitrile
Category	SIF-Silicone Free
Size range	EU 6-12
Sample weight	0.020 kg
Norms	EN ISO 21420:2020 EN 388:2016



EN ISO 21420

EN 388:2016



Industries:

Assembly, Automotive, Chemical, Cleaning, Construction, Industry, Logistics, Mining, Oil & Gas, Tactical

Touchscreen compatible

You can use your smartphone or tablet without taking off the gloves, thanks to their special coating.

DMF-free PU

Made from polyurethane that doesn't contain DMF (a chemical that can be harmful), which means they are safe to use.



174

Performance level 4131A

EN388:2016	0	1	2	3	4	5
a. Abrasion resistance (cycles)	< 100	100	500	2000	8000	-
b. Cut resistance (Coup test)	< 1.2	1.2	2.5	5.0	10.0	20.0
c. Tear resistance (newton)	< 10	10	25	50	75	-
d. Puncture resistance (newton)	< 20	20	60	100	150	-

EN ISO 13997 (TDM-100 test)	A	B	C	D	E	F
e. Straight blade cut resistance (TDM 100 test)	2	5	10	15	22	30

- a. Abrasion resistance: based on the number of cycles required to rub through the sample glove.
- b. Cut resistance: based on the number of cycles required to cut through the sample at a constant speed with a rotating blade.
- c. Tear resistance: based on the amount of force required to tear the sample.
- d. Puncture resistance: based on the amount of force required to pierce the sample with a standard sized point.
- e. Cut resistance according TDM100 test based on the number of cycles required to cut through the sample at a constant speed with a sliding blade.

SAFETY JOGGER
WORKS

HEAD-TO-TOE PROTECTION

ENGINEERED IN EUROPE

www.safetyjogger.com