

AQUA GRIP

AQUAGRIP

Professional antislip shoe

- Composition: EVA and outsole made of rubber
- Professional use or leisure : Secure movements on slippery floors in wet environments
- Outstanding grip coefficient
- Built-in water drainage system
- Tiger-grip ® antislip sole Spirit of Grip with self cleaning studs

Upper	EVA
Lining	N/A
Footbed	N/A
Outsole	EVA / Rubber (NBR)
Size range	EU 35-46 / UK 3.0-11.0 / US 3.0-12.0 JPN 21.5-30 / KOR 230-300

CO_2 0.00 kg



GRY



WHT

Industries:
Cleaning

Environments:
Extreme slippery surfaces, Snowy and icy

Test results:

	Description		Result	Measure unit
Upper	**EVA**			
	Upper: permeability to water vapor	≥ 0.8	N/A	mg/cm^2 /h
	Upper: water vapor coefficient	≥ 15	N/A	mg/cm^2
Lining	**N/A**			
	Lining: permeability to water vapor	≥ 2	N/A	mg/cm^2 /h
	Lining: water vapor coefficient	≥ 20	N/A	mg/cm^2
Footbed	**N/A**			
	Footbed: abrasion resistance (dry/wet) (cycles)	25600/12800	25600/12800	cycles
Outsole	**EVA / Rubber (NBR)**			
	Outsole abrasion resistance (volume loss)	≤ 150	140	mm^3
	Outsole slip resistance SRA: heel	≥ 0.28	0.50	friction
	Outsole slip resistance SRA: flat	≥ 0.32	0.48	friction
	Outsole slip resistance SRB: heel	≥ 0.13	0.35	friction
	Outsole slip resistance SRB: flat	≥ 0.18	0.32	friction
	Antistatic value	0.1 - 1000	N/A	MegaOhm
	ESD value	0.1 - 100	N/A	MegaOhm
	Heel energy absorption	≥ 20	N/A	J

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Carbon footprint:

	Description	Result	Measure unit
CO2 emission			
	Material	0.00	kg
		0.00 kg CO2/pair	

CO2 calculation:
Values are rounded to two decimals.
These analyses are performed using our in-house environmental calculators, developed within the Cortina Group. The CO2 values are valid at the time of calculation and may be subject to change.