



Medium

## ARMOUR 02

Mid-cut all-round tactical boot

Safety Jogger's Armour is a versatile, mid-cut tactical boot boasting heat-resistant, antistatic, and waterproof features. Its oil-resistant outsole provides firm grip and its lining ensures all-day comfort.

Upper	Waterproof Leather
Lining	Sympatex Membrane
Footbed	SJ foam footbed
Outsole	Phylon/Rubber
Category	O2 / WR, HI, CI, FO, HRO, SRC
Size range	EU 36-48 / UK 3.5-13.0 / US 4.0-13.5 JPN 22.5-31.5 / KOR 235-315
Sample weight	0.590 kg
Norms	ASTM F2892:2018 EN ISO 20347:2012




BLK



**Sympatex® lining**  
Keeps your feet dry and comfortable in all weather conditions.



**Waterproof (WR)**  
Waterproof footwear prevents liquids to enter into the shoe.



**Heat resistant outsole (HRO)**  
The outsole resists high temperatures up to 300°C.



**Antistatic**  
Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm



**Oil & fuel resistant**  
The outsole is resistant against oil and fuel.

**Industries:**

Tactical, Uniform

**Environments:**

Muddy environment, Uneven surfaces, Wet environment

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
<b>Upper</b>	<b>Waterproof Leather</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	4.2	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	39	≥ 15
<b>Lining</b>	<b>Sympatex Membrane</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	3.4	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	27	≥ 20
<b>Footbed</b>	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
<b>Outsole</b>	<b>Phylon/Rubber</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	68	≤ 150
	Outsole slip resistance SRA: heel	friction	0.42	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.41	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.19	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.23	≥ 0.18
	Antistatic value	MegaOhm	136.9	0.1 - 1000
ESD value	MegaOhm	N/A	0.1 - 100	
	Heel energy absorption	J	34	≥ 20

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.