



SAFETY JOGGER

PROFESSIONAL



Medium

ATEN 06 LOW

ATEN06LOW

Waterproof Work Sneaker

Waterproof work sneakers with a recycled lining, protective scuff cap, ESD protection, and ultimate Tiger Grip.

Upper	Membrane, Textile
Lining	Recycled Mesh (100% recycled)
Footbed	SJ Recycled Memory Foam Footbed (90% recycled)
Midsole	N/A
Outsole	Phylon/Rubber (NBR)
Category	06 / SR, SC, HRO, ESD
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
Sample weight	0.392 kg
Norms	EN ISO 20347:2022+A1:2024 ASTM F2892:2024



BLK



Waterproof (WR)

Waterproof footwear prevents liquids to enter into the shoe.



Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Heat resistant outsole (HRO)

The outsole resists high temperatures up to 300°C.



Slip resistance (SR)

Replaces the previously used term of SRA+SRB=SRC. SR means the slip test has been executed on tiles contaminated with soap and with oil.



Scuff Cap (SC)

Separately tested material to cover the toe cap area to reduce abrasion of the upper material (e.g. during kneeling operations) and extend usability of the safety shoe.



Tiger Grip Technology

Outsoles with Tiger Grip technology are renowned for their slip resistance, ability to withstand wear and tear and excellent traction with different surfaces, even wet and uneven ones. They are crafted with an exclusive rubber compound and engineered with specific patterns and grooves to enhance grip and stability.

SAFETY
JOGGER
WORKS

HEAD-TO-TOE
PROTECTION

ENGINEERED
IN EUROPE

www.safetyjogger.com

Industries:

Catering, Cleaning, Assembly, Medical, Uniform

Environments:

Dry environment, Wet environment, Warm surfaces, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	Membrane, Textile			
	Upper: permeability to water vapor	mg/cm² /h	10.5	≥ 0.8
	Upper: water vapor coefficient	mg/cm²	84.4	≥ 15
Lining	Recycled Mesh (100% recycled)			
	Lining: permeability to water vapor	mg/cm² /h	86.31	≥ 2
	Lining: water vapor coefficient	mg/cm²	691	≥ 20
Footbed	SJ Recycled Memory Foam Footbed (90% recycled)			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	Phylon/Rubber (NBR)			
	Outsole abrasion resistance (volume loss)	mm³	91	≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.4	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.39	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.28	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.29	≥ 0.22
	Antistatic value	MegaOhm	41.2	0.1 - 1000
	ESD value	MegaOhm	17.8	0.1 - 100
	Heel energy absorption	J	44	≥ 20

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.