SAFETY JOGGER
INDUSTRIAL



Heavy

BESTBOOT2 S3

Full Leather Work Boot With Warm Lining

BESTBOOT2 combines strength and comfort with steel protection, antistatic safety, oil resistance, and support that keeps feet cool, dry, and pain-free.

Upper	Barton Action Leather
Lining	Cambrella
Footbed	SJ Recycled Foam Footbed (96% recycled)
Midsole	Steel
Outsole	BASF PU/BASF PU
Toecap	Steel
Category	S3 / SR, SC, LG, FO, CI
Size range	EU 36-47 / UK 3.5-12.0 / US 4.0-13.0 JPN 22.5-31 / KOR 235-310
Sample weight	0.809 kg
Norms	EN ISO 20345:2022+A1:2024 ASTM F2413:2024



BLK

CO_2 15.55 kg

WPA · 3FIT SYSTEM · NESKRID



Oil & fuel resistant
The outsole is resistant against oil and fuel.



S3
S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



Antistatic
Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm



Steel midsole
Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



Steel toecap
Robust metal support to protect the feet of the wearer against falling or rolling objects.



Self-cleaning outsole
Self-cleaning outsoles are designed to reduce clogging of the profile.

Industries:
Chemical, Construction, Mining, Oil & Gas, Industry

Environments:
Muddy environment, Uneven surfaces

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

Test results:

	Description	EN ISO 20345	Result	Measure unit
Upper	**Barton Action Leather**			
	Upper: permeability to water vapor	≥ 0.8	1.97	mg/cm^2 /h
	Upper: water vapor coefficient	≥ 15	20	mg/cm^2
Lining	**Cambrella**			
	Lining: permeability to water vapor	≥ 2	25.39	mg/cm^2 /h
	Lining: water vapor coefficient	≥ 20	204	mg/cm^2
Footbed	**SJ Recycled Foam Footbed (96% recycled)**			
	Footbed: abrasion resistance (dry/wet) (cycles)	25600/12800	25600/12800	cycles
Outsole	**BASF PU/BASF PU**			
	Outsole abrasion resistance (volume loss)	≤ 150	N/A	mm^3
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	≥ 0.31	0.44	friction
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	≥ 0.36	0.41	friction
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	≥ 0.19	0.29	friction
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	≥ 0.22	0.29	friction
	Antistatic value	0.1 - 1000	43.8	MegaOhm
	ESD value	0.1 - 100	N/A	MegaOhm
	Heel energy absorption	≥ 20	31	J
Toecap	**Steel**			
	Impact resistance toecap (clearance after impact 100J)	N/A	N/A	mm
	Compression resistance toecap (clearance after compression 10kN)	N/A	N/A	mm
	Impact resistance toecap (clearance after impact 200J)	≥ 14	16.5	mm
	Compression resistance toecap (clearance after compression 15kN)	≥ 14	21.0	mm

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Carbon footprint:

	Description	Result	Measure unit
CO2 emission			
	Material	13.28	kg
	Packing	0.12	kg
	Manufacturing	1.90	kg
	Transport	0.26	kg
		15.55 kg CO2/pair	

	Description	Result
Recycled content		
	Product	3%
	Packing	99%

CO2 calculation:
Values are rounded to two decimals.
These analyses are performed using our in-house environmental calculators, developed within the Cortina Group. The CO2 values are valid at the time of calculation and may be subject to change.