

BESTCLOG OB

Fashionable ultra-light clog for all day comfort

Our BESTCLOG clog: ultra-lightweight, durable, hygienic, and comfortable. Washable, sterilizable, and offers excellent grip.

Upper	Expanded EVA
Lining	N/A
Footbed	SJ foam footbed
Outsole	EVA/Rubber
Category	OB / SRC
Size range	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 JPN 21.5-31 / KOR 230-310
Sample weight	0.250 kg
Norms	EN ISO 20347:2012



















Washable 30°C

These shoes can be washed in a washing machine at 30°C.



Chemically & UV sterilizeable

This shoe is chemically and UV sterilizeable.



Industries:

Catering, Cleaning, Food & beverages, Medical

Environments:

Dry environment, Wet environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347	
Upper	Expanded EVA				
	Upper: permeability to water vapor	mg/cm²/h	N/A	≥ 0.8	
	Upper: water vapor coefficient	mg/cm²	N/A	≥ 15	
Lining	N/A				
	Lining: permeability to water vapor	mg/cm²/h	N/A	≥ 2	
	Lining: water vapor coefficient	mg/cm²	N/A	≥ 20	
Footbed	SJ foam footbed				
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800	
Outsole	EVA/Rubber				
	Outsole abrasion resistance (volume loss)	mm³	96	≤ 150	
	Outsole slip resistance SRA: heel	friction	0.35	≥ 0.28	
	Outsole slip resistance SRA: flat	friction	0.35	≥ 0.32	
	Outsole slip resistance SRB: heel	friction	0.21	≥ 0.13	
	Outsole slip resistance SRB: flat	friction	0.22	≥ 0.18	
	Antistatic value	MegaOhm	N/A	0.1 - 1000	
	ESD value	MegaOhm	N/A	0.1 - 100	
	Heel energy absorption	J	N/A	≥ 20	

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



