



BESTLIGHT OB

safety clogs

The Safety Jogger BESTLIGHT clogs offer SR slip-resistance, easy cleaning at 30°C, chemical and UV sterilization, and a hygienic waterproof solution.

Upper	Expanded EVA
Footbed	Print, SJ Basic 2
Outsole	EVA/Rubber (NBR)
Category	OB / SRC
Size range	EU 36-47 / UK 3.5-12.0 / US 4.0-13.0 JPN 22.5-31 / KOR 235-310
Sample weight	0.197 kg
Norms	EN ISO 20347:2012



BLK



WHT



Hygienic waterproof solution

This shoe is made with materials that are waterproof, antibacterial and extremely light & flexible. This makes it a safe, hygienic and comfortable solution for applications in wet environments, such as cleaning or escorting patients into the shower.



Chemically & UV sterilizeable

This shoe is chemically and UV sterilizeable.



Washable 30°C

These shoes can be washed in a washing machine at 30°C.



SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.

Industries:

Catering, Cleaning, Food & beverages, Medical

Environments:

Dry environment, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	Expanded EVA			
	Upper: permeability to water vapor	mg/cm ² /h	N/A	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	N/A	≥ 15
Footbed	Print, SJ Basic 2			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	EVA/Rubber (NBR)			
	Outsole abrasion resistance (volume loss)	mm ³	83	≤ 150
	Outsole slip resistance SRA: heel	friction	0.45	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.46	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.22	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.32	≥ 0.18
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	N/A	≥ 20

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.