



**SAFETY
JOGGER**
PROFESSIONAL



Light

BIANCA OB

Casual and comfortable clog for her

The BIANCA clog is a hard worker's dream. This medical shoe with velcro closure features Coolmax lining and superior support for body posture. Perfect for medical or cleaning industries, it provides excellent grip even on slippery surfaces.

| | |
|---------------|--|
| Upper | Synthetic Leather |
| Lining | Mesh |
| Footbed | Mesh |
| Outsole | Cork/Rubber |
| Category | OB / SRC |
| Size range | EU 35-42 / UK 3.0-8.0 / US 5.5-10.5 JPN 21.5-26.5 / KOR 230-270 |
| Sample weight | 0.252 kg |
| Norms | ASTM F3445:2021 EN ISO 20347:2012 |



MUG



BLK

WHT



Coolmax® lining

Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.

**SAFETY
JOGGER**
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com

Industries:

Cleaning, Medical

Environments:

Dry environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20347 |
|----------------|---|-----------------------|-------------|--------------|
| Upper | Synthetic Leather | | | |
| | Upper: permeability to water vapor | mg/cm ² /h | 31.39 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | 252 | ≥ 15 |
| Lining | Mesh | | | |
| | Lining: permeability to water vapor | mg/cm ² /h | 64.77 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm ² | 518 | ≥ 20 |
| Footbed | Mesh | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| Outsole | Cork/Rubber | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 137 | ≤ 150 |
| | Outsole slip resistance SRA: heel | friction | 0.48 | ≥ 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.46 | ≥ 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.36 | ≥ 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.37 | ≥ 0.18 |
| | Antistatic value | MegaOhm | N/A | 0.1 - 1000 |
| | ESD value | MegaOhm | N/A | 0.1 - 100 |
| | Heel energy absorption | J | N/A | ≥ 20 |

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.