

Heavy

CALDERA S7S

CALDERAS7S


Waterproof Leather Rigger Boot

The Safety Jogger CALDERA S7S waterproof rigger boot with rubber outsole is heat-resistant, metal-free, and designed for harsh environments.

Upper	Crazy Horse Leather
Lining	Membrane
Footbed	SJ foam footbed
Midsole	Anti-puncture Textile
Outsole	Rubber (NBR), BASF PU
Toecap	Nano Carbon
Category	S7S / SR, SC, LG, FO, HI, HRO, CI, ESD
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
Sample weight	0.860 kg
Norms	EN ISO 20345:2022+A1:2024 ASTM F2413:2024




BRN


Electrostatic Discharge (ESD)
ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.




Heat resistant outsole (HRO)
The outsole resists high temperatures up to 300°C.



Ladder Grip (LG)
Especially defined contour in the shank area of a safety shoe to provide additional safety while standing on ladders.



Metal free
Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



Nano carbon toecap
Ultralight high-tech material, metalfree with no thermal or electrical conductivity.



Waterproof (WR)
Waterproof footwear prevents liquids to enter into the shoe.

Industries:

Chemical, Construction, Industry, Mining, Oil & Gas

Environments:

Cold environment, Extreme slippery surfaces, Muddy environment, Uneven surfaces, Warm surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Crazy Horse Leather			
	Upper: permeability to water vapor	mg/cm ² /h	5.16	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	46	≥ 15
Lining	Membrane			
	Lining: permeability to water vapor	mg/cm ² /h	4.9	≥ 2
	Lining: water vapor coefficient	mg/cm ²	41	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	Dry 25600 cycles/Wet 12800 cycles	25600/12800
Outsole	Rubber (NBR), BASF PU			
	Outsole abrasion resistance (volume loss)	mm ³	116	≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.45	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.47	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.28	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.32	≥ 0.22
	Antistatic value	MegaOhm	12.4	0.1 - 1000
	ESD value	MegaOhm	40	0.1 - 100
	Heel energy absorption	J	38	≥ 20
Toecap	Nano Carbon			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	16.0	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	21.0	≥ 14

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.