



CANDY 01

Ultra-comfortable sandal in lycra

The CANDY sandals offer superior comfort and protection with ESD technology, stretchable upper, and removable footbed. Ideal for medical and cleaning professionals, they provide body posture pain relief and a firm grip.

Upper	Synthetic Leather, Textile
Lining	Coolmax Mesh
Footbed	Coolmax Mesh
Outsole	EVA, Rubber (NBR)
Category	O1 / ESD, SRC
Size range	EU 35-42 / UK 3.0-8.0 / US 5.5-10.5 JPN 21.5-26.5 / KOR 230-270
Sample weight	0.224 kg
Norms	ASTM F2892:2018 EN ISO 20347:2012



BLK



FUX



LBL



LGN



LIC



WHT



Stretchable upper

Super elastic and stretchable textile for improved comfort and fit.



Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.

Industries:

Cleaning, Medical

Environments:

Dry environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	Synthetic Leather, Textile			
	Upper: permeability to water vapor	mg/cm ² /h	1.77	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	18.63	≥ 15
Lining	Coolmax Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	14.5	≥ 2
	Lining: water vapor coefficient	mg/cm ²	116.1	≥ 20
Footbed	Coolmax Mesh			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	EVA, Rubber (NBR)			
	Outsole abrasion resistance (volume loss)	mm ³	61.0	≤ 150
	Outsole slip resistance SRA: heel	friction	0.44	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.51	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.21	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.27	≥ 0.18
	Antistatic value	MegaOhm	30.8	0.1 - 1000
	ESD value	MegaOhm	62	0.1 - 100
	Heel energy absorption	J	29	≥ 20

Sample size: 37

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.