



SAFETY JOGGER

PROFESSIONAL



COLETTE 01

Elegant without compromising

Colette is an elegant and safe shoe for her that meets the latest fashion trends and it also meets the highest safety standards.

| | |
|---------------|--|
| Upper | Synthetic Leather |
| Lining | Coolmax Mesh |
| Footbed | Coolmax Mesh |
| Outsole | EVA, Rubber (NBR) |
| Category | O1 / ESD, SRC, FO |
| Size range | EU 35-42 / UK 3.0-8.0 / US 5.5-10.5 JPN 21.5-26.5 / KOR 230-270 |
| Sample weight | 0.243 kg |
| Norms | ASTM F2892:2018 EN ISO 20347:2012 |



BLK



WHT




Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Oxygrip / SJ Grip

Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.



Coolmax® lining

Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.



Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.

SAFETY JOGGER
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

**ENGINEERED
IN EUROPE**

www.safetyjogger.com

Industries:
Catering, Medical, Uniform

Environments:
Dry environment, Extreme slippery surfaces

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20347 |
|---------|---|--------------|-------------|--------------|
| Upper | Synthetic Leather | | | |
| | Upper: permeability to water vapor | mg/cm²/h | 6.5 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm² | 55 | ≥ 15 |
| Lining | Coolmax Mesh | | | |
| | Lining: permeability to water vapor | mg/cm²/h | 20 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm² | 110 | ≥ 20 |
| Footbed | Coolmax Mesh | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| Outsole | EVA, Rubber (NBR) | | | |
| | Outsole abrasion resistance (volume loss) | mm³ | 140 | ≤ 150 |
| | Outsole slip resistance SRA: heel | friction | 0.44 | ≥ 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.35 | ≥ 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.2 | ≥ 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.18 | ≥ 0.18 |
| | Antistatic value | MegaOhm | N/A | 0.1 - 1000 |
| | ESD value | MegaOhm | 40 | 0.1 - 100 |
| | Heel energy absorption | J | 43 | ≥ 20 |

Sample size: 37

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com