



SAFETY JOGGER

TACTICAL



Light

DRAGON S3

Mid-cut lightweight allround tactical boot

The Safety Jogger DRAGON is a mid-cut lightweight tactical boot for all-round use, offering superior protection, comfort, and slip resistance. Ideal for professionals in automotive, electronics, and more.

Upper	Textile, Waterproof Leather
Lining	Mesh
Footbed	SJ foam footbed
Midsole	Nonwoven
Outsole	Phylon/Rubber (NBR)
Toecap	Nano Carbon
Category	S3 / ESD, SRC
Size range	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 JPN 21.5-31 / KOR 230-310
Sample weight	0.600 kg
Norms	ASTM F2413:2018 EN ISO 20345:2011




BLK



S3

S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.




SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Metal free

Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



Nano carbon toecap

Ultralight high-tech material, metalfree with no thermal or electrical conductivity.

SAFETY
JOGGER
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com

Industries:

Automotive, Food & beverages, Logistics, Industry, Tactical, Uniform

Environments:

Extreme slippery surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Textile, Waterproof Leather			
	Upper: permeability to water vapor	mg/cm²/h	3.5	≥ 0.8
	Upper: water vapor coefficient	mg/cm²	33	≥ 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm²/h	68.4	≥ 2
	Lining: water vapor coefficient	mg/cm²	547	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	Phylon/Rubber (NBR)			
	Outsole abrasion resistance (volume loss)	mm³	65	≤ 150
	Outsole slip resistance SRA: heel	friction	0.46	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.39	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.14	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.18	≥ 0.18
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	22	0.1 - 100
	Heel energy absorption	J	21	≥ 20
Toecap	Nano Carbon			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	16.0	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	17.0	≥ 14

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com