

Medium

DUBLIN 02

Breathable Uniform Shoes

DUBLIN uniform shoes offer SR slip resistance and breathable leather for long shifts with SJ Grip and removable footbed ensuring comfort and safety.

CO_2 8.37 kg

Upper	Nappa Leather
Lining	Textile
Footbed	SJ Recycled Foam Footbed (85% recycled)
Outsole	PU/Rubber (NBR)
Category	02 / SR, FO, HRO
Size range	EU 39-48 / UK 6.0-13.0 / US 6.5-13.5 JPN 25-31.5 / KOR 255-315
Sample weight	0.429 kg
Norms	EN ISO 20347:2022+A1:2024 ASTM F2892:2024



BLK



Slip resistance (SR)
Replaces the previously used term of SRA+SRB=SRC. SR means the slip test has been executed on tiles contaminated with soap and with oil.



Breathable leather upper
Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



SJ Foam
Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.



Removable insole
Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.



Oxygrip / SJ Grip
Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.

Industries:
Catering, Food & beverages, Industry

Environments:
Dry environment, Wet environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

Test results:

	Description	EN ISO 20347	Result	Measure unit
Upper	**Nappa Leather**			
	Upper: permeability to water vapor	≥ 0.8	2.3	mg/cm^2 /h
	Upper: water vapor coefficient	≥ 15	20.3	mg/cm^2
Lining	**Textile**			
	Lining: permeability to water vapor	≥ 2	55.9	mg/cm^2 /h
	Lining: water vapor coefficient	≥ 20	447.4	mg/cm^2
Footbed	**SJ Recycled Foam Footbed (85% recycled)**			
	Footbed: abrasion resistance (dry/wet) (cycles)	25600/12800	25600/12800	cycles
Outsole	**PU/Rubber (NBR)**			
	Outsole abrasion resistance (volume loss)	≤ 150	88.9	mm^3
	Outsole slip resistance SRA: heel	≥ 0.28	0.49	friction
	Outsole slip resistance SRA: flat	≥ 0.32	0.41	friction
	Outsole slip resistance SRB: heel	≥ 0.13	0.32	friction
	Outsole slip resistance SRB: flat	≥ 0.18	0.37	friction
	Antistatic value	0.1 - 1000	17.2	MegaOhm
	ESD value	0.1 - 100	N/A	MegaOhm
	Heel energy absorption	≥ 20	41.6	J

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Carbon footprint:

	Description	Result	Measure unit
CO2 emission			
	Material	6.11	kg
	Packing	0.10	kg
	Manufacturing	1.90	kg
	Transport	0.26	kg
		8.37 kg CO2/pair	

	Description	Result
Recycled content		
	Product	6%
	Packing	99%

CO2 calculation:
Values are rounded to two decimals.
These analyses are performed using our in-house environmental calculators, developed within the Cortina Group. The CO2 values are valid at the time of calculation and may be subject to change.