



SAFETY JOGGER

PROFESSIONAL



Medium

DUBLIN 02

breathable uniform shoe for professionals

The DUBLIN shoes are a blend of comfort and safety. With SR slip resistance, a removable footbed, SJ Grip, and breathable leather upper, they are perfect for professionals in various industries.

Upper	Nappa Leather
Lining	Microsuede
Footbed	SJ foam footbed
Outsole	PU/Rubber (NBR)
Category	O2 / SRC
Size range	EU 39-48 / UK 6.0-13.0 / US 6.5-13.5 JPN 25-31.5 / KOR 255-315
Sample weight	0.429 kg
Norms	ASTM F2892:2018 EN ISO 20347:2012



BLK



SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.




Breathable leather upper

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.




SJ Foam

Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.



Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.



Oxygrip / SJ Grip

Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.

SAFETY JOGGER
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

**ENGINEERED
IN EUROPE**

www.safetyjogger.com

Industries:
Catering, Food & beverages, Industry

Environments:
Dry environment, Wet environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	Nappa Leather			
	Upper: permeability to water vapor	mg/cm²/h	2.3	≥ 0.8
	Upper: water vapor coefficient	mg/cm²	20.3	≥ 15
Lining	Microsuede			
	Lining: permeability to water vapor	mg/cm²/h	55.9	≥ 2
	Lining: water vapor coefficient	mg/cm²	447.4	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	PU/Rubber (NBR)			
	Outsole abrasion resistance (volume loss)	mm³	88.9	≤ 150
	Outsole slip resistance SRA: heel	friction	0.49	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.41	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.32	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.37	≥ 0.18
	Antistatic value	MegaOhm	17.2	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	41.6	≥ 20

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com