





Datasheet

Vertiline Lanyard



Notified Body	CE 2756		
Article No. EAN & length	EKM2110010	6425670023441	10 meter
	EKM2110020	6425670014968	20 meter
	EKM2110030	6425670023458	30 meter
	EKM2110040	8718657720302	40 meter
Standardization	EN1891:1998 type A	Low stretch kernmantel ropes.	
Materials used	Rope	14 mm, polyamide, kernmantle rope.	
	Connectors	Steel, 2 x 223 (Annapurna).	
Description	<ul style="list-style-type: none">  This semi-static kernmantle-rope is a versatile multi-use rope;  It has a low elongation factor;  A high tensile strength and an excellent abrasion protection;  Good protection against climatic influences and penetration of dirt. 		
Technical specifications	Rope diameter	14 mm	
	Elongation	3%	
	Weight rope	123 gr/m	
	Breaking load rope	30 kN	
	Breaking load connector	25 kN (= breaking load of the set.)	
Weight	EKM2110010	1.702 grams	
	EKM2110020	3.026 grams	
	EKM2110030	4.262 grams	
	EKM2110040		
Packaging	Per set in a bag, manual included.		
Lifetime	<p>Up to 6 years after first use; up to 8 years after production date. Lanyards of a single user, periodically inspected by experts and recorded in inspection log, carefully handled and maintained, stored in accordance with regulations, not in contact with oil, grease or aggressive chemicals, can be used for up to 6 years. Follow the user manual!</p>		