

Datasheet

Vertiline Universal



Notified Body	CE 2756		
Article No.	EL2321610	6425670021928	2,702 grams
EAN & Weight	EL2321620	6425670018997	4,006 grams
	EL2321630	6425670019055	5,220 grams
	EL2321640	6425670025636	6,490 grams
Standardization	EN 353-2:2002	Guided type fall arresters including a flexible anchor line.	
Materials used	Rope	14 mm, polyamide, kernmantle rope.	
	Connectors	Kangri (022) = steel Quadro (232) = aluminum.	
	Rope grab	Zinc plated steel.	
Description	<ul style="list-style-type: none"> Fall arrester on flexible anchorage line; Detachable rope grab made of zinc plated steel; Kernmantle rope with sewn terminations and protective thimbles; Energy absorber with very reliable and very gentle tear behaviour; To be used by 1 person. 		
Technical specifications	Rope diameter	14 mm	
	Breaking load rope	38 kN	
	Breaking load Kangri	25 kN	
	Breaking load Quadro	40 kN	
	Breaking load fall arrester	15 kN (= breaking load of the set .)	
	Maximum weight	100 kg	
Length	EL2321610	10 mtr	
	EL2321620	20 mtr	
	EL2321630	30 mtr	
	EL2321640	40 mtr	
Packaging	Per set in a bag, manual included.		
Lifetime	<p>Up to 10 years after first use; up to 12 years after production date. Lanyards of a single user, periodically inspected by experts and recorded in inspection log, carefully handled and maintained, stored in accordance with regulations, not in contact with oil, grease or aggressive chemicals, can be used for up to 10 years. Follow the user manual!</p>		