






# Datasheet

## Vertiline Basic



<b>Notified Body</b>	CE 2756		
<b>Article No.</b>	EL2321810	6425670030401	1,986 grams
<b>EAN &amp; weight</b>	EL2321820	6425670030289	2,910 grams
	EL2321830	6425670031163	3,850 grams
	EL2321840	6425670030265	4,800 grams
<b>Standardization</b>	EN 353-2:2002	Guided type fall arresters including a flexible anchor line.	
<b>Materials used</b>	Rope	12 mm, polyamide, kernmantle rope.	
	Connectors	2 x Kangri (022) = steel	
	Rope grab	Zinc plated steel.	
<b>Description</b>	<ul style="list-style-type: none"> <li> Fall arrester on flexible anchorage line;</li> <li> Fixed rope grab made of zinc plated steel;</li> <li> Kernmantle rope with sewn terminations and protective thimbles;</li> <li> Energy absorber with very reliable and very gentle tear behaviour;</li> <li> <b>To be used by 1 person.</b></li> </ul>		
<b>Technical specifications</b>	Rope diameter	12 mm	
	Breaking load rope	28 kN	
	Breaking load Kangri	25 kN	
	Breaking load fall arrester	15 kN (= breaking load of the set .)	
	Maximum weight	100 kg	
<b>Length</b>	EL2321810	10 mtr	
	EL2321820	20 mtr	
	EL2321830	30 mtr	
	EL2321840	40 mtr	
<b>Packaging</b>	Per set in a bag, manual included.		
<b>Lifetime</b>	<p>Up to 10 years after first use; up to 12 years after production date.                      Lanyards of a single user, periodically inspected by experts and recorded in inspection log, carefully handled and maintained, stored in accordance with regulations, not in contact with oil, grease or aggressive chemicals, can be used for up to 10 years.  <b>Follow the user manual!</b></p>		