



# SAFETY JOGGER

PROFESSIONAL



Medium

## ELIANE 01

**Sporty design with adjustable velcro strap**

The sporty ELIANE shoes offer superior grip, ESD protection, a removable footbed, an adjustable velcro strap and a breathable upper for optimal comfort. Suitable for various industries and environments, these shoes ensure less sweaty feet and improved body posture.

|               |  |
|---------------|--|
| Upper         | Synthetic Leather  |
| Lining        | Mesh   |
| Footbed       | SJ foam footbed  |
| Outsole       | Phylon/Rubber (NBR)  |
| Category      | O1 / ESD, SRC  |
| Size range    | EU 35-42 / UK 3.0-8.0 / US 5.5-10.5<br>JPN 21.5-26.5 / KOR 230-270 |
| Sample weight | 0.251 kg   |
| Norms         | ASTM F2892:2018<br>EN ISO 20347:2012                               |



BLK



LBL




WHT



### Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.




### Oxygrip / SJ Grip

Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.




### SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



### Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.



### Rubber outsole

Rubber outsoles provide versatile functions that make them suitable for many areas of application: excellent cut resistance, heat and cold resistance, high flexibility at cold temperatures, resistance against oil, fuel and many chemicals.



### Breathable upper

Increased moisture and temperature management for extended wearer comfort.

**SAFETY JOGGER**  
WORKS

**Solutions for every workplace**

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

**ENGINEERED  
IN EUROPE**

[www.safetyjogger.com](http://www.safetyjogger.com)

**Industries:**  
Catering, Cleaning, Food & beverages, Medical

**Environments:**  
Dry environment, Extreme slippery surfaces

**Maintenance instructions:**  
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

|         | Description                                     | Measure unit | Result      | EN ISO 20347 |
|---------|---|--------------|-------------|--------------|
| Upper   | <b>Synthetic Leather</b>                        |              |             |              |
|         | Upper: permeability to water vapor              | mg/cm²/h     | 1.4         | ≥ 0.8        |
|         | Upper: water vapor coefficient                  | mg/cm²       | 15.5        | ≥ 15         |
| Lining  | <b>Mesh</b>                                     |              |             |              |
|         | Lining: permeability to water vapor             | mg/cm²/h     | 43.7        | ≥ 2          |
|         | Lining: water vapor coefficient                 | mg/cm²       | 350         | ≥ 20         |
| Footbed | <b>SJ foam footbed</b>                          |              |             |              |
|         | Footbed: abrasion resistance (dry/wet) (cycles) | cycles       | 25600/12800 | 25600/12800  |
| Outsole | <b>Phylon/Rubber (NBR)</b>                      |              |             |              |
|         | Outsole abrasion resistance (volume loss)       | mm³          | 75          | ≤ 150        |
|         | Outsole slip resistance SRA: heel               | friction     | 0.36        | ≥ 0.28       |
|         | Outsole slip resistance SRA: flat               | friction     | 0.37        | ≥ 0.32       |
|         | Outsole slip resistance SRB: heel               | friction     | 0.24        | ≥ 0.13       |
|         | Outsole slip resistance SRB: flat               | friction     | 0.31        | ≥ 0.18       |
|         | Antistatic value                                | MegaOhm      | N/A         | 0.1 - 1000   |
|         | ESD value                                       | MegaOhm      | 75          | 0.1 - 100    |
|         | Heel energy absorption                          | J            | 24          | ≥ 20         |

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED  
IN EUROPE

www.safetyjogger.com