



SAFETY JOGGER

INDUSTRIAL



Light

GOBI S1P

GOBIS1P

Low-cut S1P Safety Shoes

Modern S1P safety shoes with suede leather upper, steel toe, memory foam comfort, and an abrasion-resistant scuff cap.

Upper	Suede Leather, Mesh
Lining	Recycled Mesh (100% recycled)
Footbed	SJ Recycled Memory Foam Footbed (90% recycled)
Midsole	Steel
Outsole	PU/PU
Toecap	Steel
Category	S1 P / SR, SC, LG, FO, CI
Size range	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 JPN 21.5-31 / KOR 230-310
Sample weight	0.625 kg
Norms	EN ISO 20345:2022+A1:2024 ASTM F2413:2024



BLK



NAV




Scuff Cap (SC)

Separately tested material to cover the toe cap area to reduce abrasion of the upper material (e.g. during kneeling operations) and extend usability of the safety shoe.



Slip resistance (SR)

Replaces the previously used term of SRA+SRB=SRC. SR means the slip test has been executed on tiles contaminated with soap and with oil.



Oil & fuel resistant

The outsole is resistant against oil and fuel.



Ladder Grip (LG)

Especially defined contour in the shank area of a safety shoe to provide additional safety while standing on ladders.



Breathable leather upper

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



Cold insulated (CI)

Cold insulated (CI) safety shoes keep your feet warm. They are worn in cold environments.

SAFETY JOGGER
WORKS

HEAD-TO-TOE PROTECTION

ENGINEERED
IN EUROPE

www.safetyjogger.com

Industries:
Automotive, Construction, Logistics, Industry, Assembly

Environments:
Dry environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Suede Leather, Mesh			
	Upper: permeability to water vapor	mg/cm ² /h	12.7	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	101.6	≥ 15
Lining	Recycled Mesh (100% recycled)			
	Lining: permeability to water vapor	mg/cm ² /h	86.31	≥ 2
	Lining: water vapor coefficient	mg/cm ²	691	≥ 20
Footbed	SJ Recycled Memory Foam Footbed (90% recycled)			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	PU/PU			
	Outsole abrasion resistance (volume loss)	mm ³	137	≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.40	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.41	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.29	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.30	≥ 0.22
	Antistatic value	MegaOhm	33.6	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	30	≥ 20
Toecap	Steel			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	15	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	20.5	≥ 14

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.