

SAFETY JOGGER INDUSTRIAL

Heavy

GORA S7S HIGH

GORAS7

High safety boot with breathable leather upper and Tiger Grip Technology

GORA S7S waterproof safety boots keeps your feet dry and delivers heat resistance, superior grip and lightweight comfort for tough industrial work.

Upper	Full Grain Leather
Lining	3D-Mesh, Membrane
Footbed	SJ Recycled Foam Footbed (96% recycled)
Midsole	Anti-Puncture Textile
Outsole	PU/Rubber (NBR)
Toecap	Composite
Category	S7S / SR, SC, LG, FO, HI, HRO, CI, ESD
Size range	EU 36-48 / UK 3.5-13.0 / US 4.0-13.5 JPN 22.5-31.5 / KOR 235-315
Sample weight	0.920 kg
Norms	ASTM F2413:2018 EN ISO 20345:2022



BLK

CO_2 15.04 kg



Breathable leather upper
Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



Composite toecap
Metalfree and lightweight, no thermal or electrical conductivity



Heat resistant outsole (HRO)
The outsole resists high temperatures up to 300°C.



Oil & fuel resistant
The outsole is resistant against oil and fuel.



Puncture resistant lightweight
Metal free, super flexible and ultralight puncture resistant midsole. Covers 100% of the bottom area of the last, no thermal conductivity.



Scuff Cap (SC)
Separately tested material to cover the toe cap area to reduce abrasion of the upper material (e.g. during kneeling operations) and extend usability of the safety shoe.

Industries:
Mining, Construction, Oil & Gas, Industry

Environments:
Cold environment, Extreme slippery surfaces, Muddy environment, Uneven surfaces, Wet environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

Test results:

	Description	EN ISO 20345	Result	Measure unit
Upper	**Full Grain Leather**			
	Upper: permeability to water vapor	≥ 0.8	3.3	mg/cm^2 /h
	Upper: water vapor coefficient	≥ 15	36	mg/cm^2
Lining	**3D-Mesh, Membrane**			
	Lining: permeability to water vapor	≥ 2	6.3	mg/cm^2 /h
	Lining: water vapor coefficient	≥ 20	51	mg/cm^2
Footbed	**SJ Recycled Foam Footbed (96% recycled)**			
	Footbed: abrasion resistance (dry/wet) (cycles)	25600/12800	25600/12800	cycles
Outsole	**PU/Rubber (NBR)**			
	Outsole abrasion resistance (volume loss)	≤ 150	122	mm^3
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	≥ 0.31	0.41	friction
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	≥ 0.36	0.37	friction
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	≥ 0.19	0.28	friction
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	≥ 0.22	0.25	friction
	Antistatic value	0.1 - 1000	54	MegaOhm
	ESD value	0.1 - 100	58	MegaOhm
	Heel energy absorption	≥ 20	28	J
Toecap	**Composite**			
	Impact resistance toecap (clearance after impact 100J)	N/A	N/A	mm
	Compression resistance toecap (clearance after compression 10kN)	N/A	N/A	mm
	Impact resistance toecap (clearance after impact 200J)	≥ 14	17	mm
	Compression resistance toecap (clearance after compression 15kN)	≥ 14	22	mm

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Carbon footprint:

	Description	Result	Measure unit
CO2 emission			
	Material	12.76	kg
	Packing	0.12	kg
	Manufacturing	1.90	kg
	Transport	0.26	kg
		15.04 kg CO2/pair	

	Description	Result
Recycled content		
	Product	4%
	Packing	99%

CO2 calculation:
Values are rounded to two decimals.
These analyses are performed using our in-house environmental calculators, developed within the Cortina Group. The CO2 values are valid at the time of calculation and may be subject to change.