

SAFETY JOGGER PROFESSIONAL

Light

JAMES OB

Men's Lightweight Sneakers

The JAMES sporty and ultra-light sneakers offer unmatched comfort with a removable footbed, 3D mesh, and superior support.

Upper	Mesh
Lining	Recycled Mesh (100% recycled)
Footbed	SJ Recycled Foam Footbed (96% recycled)
Outsole	Phylon/Rubber (NBR)
Category	OB / SRA, E
Size range	EU 36-49 / UK 3.5-13.5 / US 4.0-14.5 JPN 22.5-32.5 / KOR 235-325
Sample weight	0.330 kg
Norms	ASTM F3445:2024 EN ISO 20347:2012

CO2 4.66 kg



NAV



BLK



LGR



3D mesh
Three-dimensional produced distance mesh to provide increased moisture and temperature management.



Coolmax® lining
Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.



Removable insole
Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.

Industries:
Catering, Food & beverages, Medical

Environments:
Dry environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

Test results:

	Description	EN ISO 20347	Result	Measure unit
Upper	**Mesh**			
	Upper: permeability to water vapor	≥ 0.8	1.4	mg/cm^2 /h
	Upper: water vapor coefficient	≥ 15	15.5	mg/cm^2
Lining	**Recycled Mesh (100% recycled)**			
	Lining: permeability to water vapor	≥ 2	28.9	mg/cm^2 /h
	Lining: water vapor coefficient	≥ 20	231.3	mg/cm^2
Footbed	**SJ Recycled Foam Footbed (96% recycled)**			
	Footbed: abrasion resistance (dry/wet) (cycles)	25600/12800	25600/12800	cycles
Outsole	**Phylon/Rubber (NBR)**			
	Outsole abrasion resistance (volume loss)	≤ 150	81	mm^3
	Outsole slip resistance SRA: heel	≥ 0.28	0.48	friction
	Outsole slip resistance SRA: flat	≥ 0.32	0.45	friction
	Outsole slip resistance SRB: heel	≥ 0.13	N/A	friction
	Outsole slip resistance SRB: flat	≥ 0.18	N/A	friction
	Antistatic value	0.1 - 1000	N/A	MegaOhm
	ESD value	0.1 - 100	N/A	MegaOhm
	Heel energy absorption	≥ 20	34	J

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Carbon footprint:

	Description	Result	Measure unit
CO2 emission			
	Material	2.40	kg
	Packing	0.10	kg
	Manufacturing	1.90	kg
	Transport	0.26	kg
		4.66 kg CO2/pair	

	Description	Result
Recycled content		
	Product	13%
	Packing	98%

CO2 calculation:
Values are rounded to two decimals.
These analyses are performed using our in-house environmental calculators, developed within the Cortina Group. The CO2 values are valid at the time of calculation and may be subject to change.