SAFETY JOGGER
PROFESSIONAL



Light

JUMADI OB

JUMADIOB

Lightweight, Breathable Wide Sneaker

JUMADI OB lightweight, ultrabreathable occupational shoes with superior slip resistance and removable footbed keeps your feet comfortable.

Upper	Mesh
Lining	Recycled Mesh (100% recycled)
Footbed	SJ Recycled Foam Footbed (96% recycled)
Outsole	EVA / Rubber (NBR)
Category	OB / SR, E
Size range	EU 35-48
Sample weight	0.310 kg
Norms	EN ISO 20347:2022+A1:2024

CO_2 4.41 kg



WHT




BLK



LBL



PNK




Breathable upper
Increased moisture and temperature management for extended wearer comfort.



Slip resistance (SR)
Replaces the previously used term of SRA+SRB=SRC. SR means the slip test has been executed on tiles contaminated with soap and with oil.



SJ Foam
Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.



Metal free
Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.

Industries:
Catering, Medical, Assembly, Logistics

Environments:
Dry environment

Test results:

	Description	EN ISO 20347	Result	Measure unit
Upper	**Mesh**			
	Upper: permeability to water vapor	≥ 0.8	30.55	mg/cm^2 /h
	Upper: water vapor coefficient	≥ 15	244	mg/cm^2
Lining	**Recycled Mesh (100% recycled)**			
	Lining: permeability to water vapor	≥ 2	30.55	mg/cm^2 /h
	Lining: water vapor coefficient	≥ 20	244	mg/cm^2
Footbed	**SJ Recycled Foam Footbed (96% recycled)**			
	Footbed: abrasion resistance (dry/wet) (cycles)	25600/12800	Dry 25600 cycles/Wet 12800 cycles	cycles
Outsole	**EVA / Rubber (NBR)**			
	Outsole abrasion resistance (volume loss)	≤ 150	60	mm^3
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	≥ 0.31	0.44	friction
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	≥ 0.36	0.38	friction
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	≥ 0.19	0.24	friction
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	≥ 0.22	0.24	friction
	Antistatic value	0.1 - 1000	N/A	MegaOhm
	ESD value	0.1 - 100	N/A	MegaOhm
	Heel energy absorption	≥ 20	34	J

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Carbon footprint:

	Description	Result	Measure unit
CO2 emission			
	Material	2.16	kg
	Packing	0.10	kg
	Manufacturing	1.90	kg
	Transport	0.26	kg
		4.41 kg CO2/pair	

	Description	Result
Recycled content		
	Product	14%
	Packing	98%

CO2 calculation:
Values are rounded to two decimals.
These analyses are performed using our in-house environmental calculators, developed within the Cortina Group. The CO2 values are valid at the time of calculation and may be subject to change.