



SAFETY JOGGER

INDUSTRIAL



Medium

JUMPER S3


Low-cut safety shoe with enhanced grip control

The low-cut Safety Jogger JUMPER combines safety with comfort. Features enhanced grip control, SR slip-resistant soles, metal-free design, antistatic feature, and heel energy absorption. Perfect for diverse industries and environments.

| | |
|---------------|---|
| Upper | Suede Leather |
| Lining | Mesh |
| Footbed | SJ foam footbed |
| Midsole | Anti-puncture Textile |
| Outsole | PU |
| Toecap | Composite |
| Category | S3 / SRC |
| Size range | EU 36-47 / UK 3.5-12.0 / US 4.0-13.0 JPN 22.5-31 / KOR 235-310 |
| Sample weight | 0.600 kg |
| Norms | ASTM F2413:2018 EN ISO 20345:2011 |



117



Metal free

Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



Antistatic

Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm



SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Heel energy absorption

Heel energy absorption reduces the impact of jumps or running on the body of the wearer.

SAFETY JOGGER
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

**ENGINEERED
IN EUROPE**

www.safetyjogger.com

Industries:

Automotive, Cleaning, Construction, Food & beverages, Logistics, Industry

Environments:

Dry environment, Uneven surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20345 |
|---------|--|--------------|-------------|--------------|
| Upper | Suede Leather | | | |
| | Upper: permeability to water vapor | mg/cm²/h | 11.7 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm² | 101.6 | ≥ 15 |
| Lining | Mesh | | | |
| | Lining: permeability to water vapor | mg/cm²/h | 86.9 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm² | 695.4 | ≥ 20 |
| Footbed | SJ foam footbed | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| Outsole | PU | | | |
| | Outsole abrasion resistance (volume loss) | mm³ | 186.2 | ≤ 150 |
| | Outsole slip resistance SRA: heel | friction | 0.39 | ≥ 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.34 | ≥ 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.15 | ≥ 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.18 | ≥ 0.18 |
| | Antistatic value | MegaOhm | 279 | 0.1 - 1000 |
| | ESD value | MegaOhm | N/A | 0.1 - 100 |
| Toecap | Composite | | | |
| | Impact resistance toecap (clearance after impact 100J) | mm | N/A | N/A |
| | Compression resistance toecap (clearance after compression 10kN) | mm | N/A | N/A |
| | Impact resistance toecap (clearance after impact 200J) | mm | 16.0 | ≥ 14 |
| | Compression resistance toecap (clearance after compression 15kN) | mm | 22.5 | ≥ 14 |

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com