



SAFETY JOGGER

PROFESSIONAL



Light

JUNO 01 TLS

JUNOO1TLS


Fashionable sneaker with TLS closure

JUNO is the successor of our Kassie safety shoe and combines a casual look with first-class comfort thanks to its lightweight design, climate-optimized materials, and heel energy absorption. JUNO also has a rubber outsole that provides excellent grip, offers anti-static properties and is washable at 30°C.


Upper	3D-Mesh
Lining	Mesh
Footbed	Print
Outsole	Recycled Phylon/Rubber
Category	O1 / SR, FO
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
Sample weight	0.258 kg
Norms	ASTM F2892:2018 EN ISO 20347:2022(Europe)



DGR


Breathable upper
Increased moisture and temperature management for extended wearer comfort.




Oxygrip / SJ Grip
Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.




SRC slip resistance
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



3D mesh
Three-dimensional produced distance mesh to provide increased moisture and temperature management.



Heel energy absorption
Heel energy absorption reduces the impact of jumps or running on the body of the wearer.



SJ Foam
Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED IN EUROPE

www.safetyjogger.com

Industries:

Catering, Food & beverages, Medical, Uniform

Environments:

Dry environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	3D-Mesh			
	Upper: permeability to water vapor	mg/cm ² /h	25.3	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	204	≥ 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	21.1	≥ 2
	Lining: water vapor coefficient	mg/cm ²	169	≥ 20
Footbed	Print			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	Recycled Phylon/Rubber			
	Outsole abrasion resistance (volume loss)	mm ³	90	≤ 150
	Outsole slip resistance SRA: heel	friction	0.42	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.41	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.18	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.23	≥ 0.18
	Antistatic value	MegaOhm	30.5	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	30	≥ 20

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.