SAFETY JOGGER
INDUSTRIAL



Medium

LABOR S3

Comfortable Safety Boots With HRO Outsole

LABOR safety boots with durable rubber outsole resist chemicals, heat, hydrocarbons, acids and hydrolysis, offering lasting comfort, protection and grip.

Upper	Barton Action Leather
Lining	Recycled Mesh (100% recycled)
Footbed	SJ Recycled Foam Footbed (96% recycled)
Midsole	Steel
Outsole	Rubber (NBR)
Toecap	Steel
Category	S3 / SR, LG, FO, HI, HRO, CI
Size range	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 JPN 21.5-31 / KOR 230-310
Sample weight	0.710 kg
Norms	EN ISO 20345:2022+A1:2024 ASTM F2413:2024





CO_2 9.89 kg

BLK



Heat resistant outsole (HRO)
The outsole resists high temperatures up to 300°C.



SRC slip resistance
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Steel midsole
Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



SJ Foam
Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.



Steel toecap
Robust metal support to protect the feet of the wearer against falling or rolling objects.



Antistatic
Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm

Industries:
Industry, Catering, Chemical, Cleaning, Food & beverages, Oil & Gas

Environments:
Cold environment, Extreme slippery surfaces, Warm surfaces

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

Test results:

	Description	EN ISO 20345	Result	Measure unit
Upper	**Barton Action Leather**			
	Upper: permeability to water vapor	≥ 0.8	0.92	mg/cm^2/h
	Upper: water vapor coefficient	≥ 15	15.0	mg/cm^2
Lining	**Recycled Mesh (100% recycled)**			
	Lining: permeability to water vapor	≥ 2	59.9	mg/cm^2/h
	Lining: water vapor coefficient	≥ 20	480	mg/cm^2
Footbed	**SJ Recycled Foam Footbed (96% recycled)**			
	Footbed: abrasion resistance (dry/wet) (cycles)	25600/12800	25600/12800	cycles
Outsole	**Rubber (NBR)**			
	Outsole abrasion resistance (volume loss)	≤ 150	92	mm^3
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	≥ 0.31	0.43	friction
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	≥ 0.36	0.42	friction
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	≥ 0.19	0.28	friction
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	≥ 0.22	0.33	friction
	Antistatic value	0.1 - 1000	20.5	MegaOhm
	ESD value	0.1 - 100	N/A	MegaOhm
	Heel energy absorption	≥ 20	32.0	J
Toecap	**Steel**			
	Impact resistance toecap (clearance after impact 100J)	N/A	N/A	mm
	Compression resistance toecap (clearance after compression 10kN)	N/A	N/A	mm
	Impact resistance toecap (clearance after impact 200J)	≥ 14	20.0	mm
	Compression resistance toecap (clearance after compression 15kN)	≥ 14	23.5	mm

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Carbon footprint:

	Description	Result	Measure unit
CO2 emission			
	Material	7.60	kg
	Packing	0.13	kg
	Manufacturing	1.90	kg
	Transport	0.26	kg
		9.89 kg CO2/pair	

	Description	Result
Recycled content		
	Product	6%
	Packing	99%

CO2 calculation:
Values are rounded to two decimals.
These analyses are performed using our in-house environmental calculators, developed within the Cortina Group. The CO2 values are valid at the time of calculation and may be subject to change.