SAFETY JOGGER
INDUSTRIAL



Light

LIGERO S1 P

Lightweight ESD Safety Shoes

Ultra-light, flexible safety shoe with SJ-3FIT adjustable width, nano carbon toe cap, and hybrid insole for unmatched comfort at work.

Upper	Mesh
Lining	Recycled 3D-Mesh (100% recycled)
Footbed	SJ Recycled Foam Footbed (96% recycled)
Midsole	Anti-Puncture Nonwoven
Outsole	Phylon/Rubber (NBR)
Toecap	Nano Carbon
Category	S1 P / SRC, CI, ESD
Size range	EU 35-49 / UK 3.0-13.5 / US 3.0-14.5 JPN 21.5-32.5 / KOR 230-325
Sample weight	0.439 kg
Norms	ASTM F2413:2024 EN ISO 20345:2011

CO_2
4.92 kg



ORA




NAV



BLK



Electrostatic Discharge (ESD)
ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Metal free
Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



Nano carbon toecap
Ultralight high-tech material, metalfree with no thermal or electrical conductivity.



Puncture resistant lightweight
Metal free, super flexible and ultralight puncture resistant midsole. Covers 100% of the bottom area of the last, no thermal conductivity.



3D mesh
Three-dimensional produced distance mesh to provide increased moisture and temperature management.



SJ Foam
Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.

Industries:
Automotive, Logistics, Industry

Environments:
Dry environment, Extreme slippery surfaces

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

Test results:

	Description	EN ISO 20345	Result	Measure unit
Upper	**Mesh**			
	Upper: permeability to water vapor	≥ 0.8	37	mg/cm^2 /h
	Upper: water vapor coefficient	≥ 15	250	mg/cm^2
Lining	**Recycled 3D-Mesh (100% recycled)**			
	Lining: permeability to water vapor	≥ 2	80	mg/cm^2 /h
	Lining: water vapor coefficient	≥ 20	550	mg/cm^2
Footbed	**SJ Recycled Foam Footbed (96% recycled)**			
	Footbed: abrasion resistance (dry/wet) (cycles)	25600/12800	25600/12800	cycles
Outsole	**Phylon/Rubber (NBR)**			
	Outsole abrasion resistance (volume loss)	≤ 150	85	mm^3
	Outsole slip resistance SRA: heel	≥ 0.28	0.46	friction
	Outsole slip resistance SRA: flat	≥ 0.32	0.39	friction
	Outsole slip resistance SRB: heel	≥ 0.13	0.14	friction
	Outsole slip resistance SRB: flat	≥ 0.18	0.18	friction
	Antistatic value	0.1 - 1000	N/A	MegaOhm
	ESD value	0.1 - 100	45	MegaOhm
	Heel energy absorption	≥ 20	20	J
Toecap	**Nano Carbon**			
	Impact resistance toecap (clearance after impact 100J)	N/A	N/A	mm
	Compression resistance toecap (clearance after compression 10kN)	N/A	N/A	mm
	Impact resistance toecap (clearance after impact 200J)	≥ 14	16	mm
	Compression resistance toecap (clearance after compression 15kN)	≥ 14	16.5	mm

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Carbon footprint:

	Description	Result	Measure unit
CO2 emission			
	Material	2.65	kg
	Packing	0.12	kg
	Manufacturing	1.90	kg
	Transport	0.26	kg
		4.92 kg CO2/pair	

	Description	Result
Recycled content		
	Product	24%
	Packing	99%

CO2 calculation:
Values are rounded to two decimals.
These analyses are performed using our in-house environmental calculators, developed within the Cortina Group. The CO2 values are valid at the time of calculation and may be subject to change.