



# SAFETY JOGGER

PROFESSIONAL



## LUCIA 01

### Closed shoe with an elegant touch

The LUCIA is a stylish shoe that prioritizes your comfort and safety. Features ESD technology and removable footbed for customizable comfort.

Outsole	Rubber (NBR)
Category	O1 / ESD, SRC
Size range	EU 34-43 / UK 2.0-9.0 / US 2.5-11.5 JPN 21.0-27 / KOR 225-280
Sample weight	0.234 kg
Norms	ASTM F2892:2018 EN ISO 20347:2012



BLK



FLR



FUX



LBL



LGN



PTB



WHT



#### Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



#### Coolmax® lining

Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.



#### Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.

**SAFETY JOGGER**  
WORKS

**Solutions for every workplace**

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

**ENGINEERED  
IN EUROPE**

[www.safetyjogger.com](http://www.safetyjogger.com)

**Industries:**

Catering, Cleaning, Food & beverages, Medical

**Environments:**

Dry environment, Extreme slippery surfaces, Uneven surfaces

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Outsole	Rubber (NBR)			
	Outsole abrasion resistance (volume loss)	mm³	117	≤ 150
	Outsole slip resistance SRA: heel	friction	0.49	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.46	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.18	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.23	≥ 0.18
	Antistatic value	MegaOhm	14.3	0.1 - 1000
	ESD value	MegaOhm	34.0	0.1 - 100
	Heel energy absorption	J	42.0	≥ 20

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.