SAFETY JOGGER PROFESSIONAL



Light

MAUD OB

Women's Lightweight Sneakers

Lightweight and breathable, MAUD medical shoes deliver comfort, slip resistance, and safety for professionals on their feet all day.

Upper	Mesh
Lining	Recycled Mesh (100% recycled)
Footbed	SJ Recycled Foam Footbed (96% recycled)
Outsole	Phylon/Rubber (NBR)
Category	OB / SRA, E
Size range	EU 35-42 / UK 3.0-8.0 / US 5.5-10.5 JPN 21.5-26.5 / KOR 230-270
Sample weight	0.265 kg
Norms	ASTM F2892:2024 EN ISO 20347:2012

CO_2 4.24 kg



LGR



FUX



BLK



NAV



WHT



3D mesh
Three-dimensional produced distance mesh to provide increased moisture and temperature management.



Removable insole
Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.



Breathable upper
Increased moisture and temperature management for extended wearer comfort.



Oxygrip / SJ Grip
Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.



SRA slip resistance
Slip resistance is one of the most important features of safety and occupational footwear. SRA slip resistant soles are tested on a ceramic tile with dilute soap solution.

SAFETY JOGGER WORKS

HEAD-TO-TOE PROTECTION

ENGINEERED IN EUROPE

www.safetyjogger.com

Industries:
Catering, Cleaning, Food & beverages, Medical

Environments:
Dry environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

Test results:

	Description	EN ISO 20347	Result	Measure unit
Upper	**Mesh**			
	Upper: permeability to water vapor	≥ 0.8	1.4	mg/cm^2 /h
	Upper: water vapor coefficient	≥ 15	15.5	mg/cm^2
Lining	**Recycled Mesh (100% recycled)**			
	Lining: permeability to water vapor	≥ 2	28.9	mg/cm^2 /h
	Lining: water vapor coefficient	≥ 20	231.3	mg/cm^2
Footbed	**SJ Recycled Foam Footbed (96% recycled)**			
	Footbed: abrasion resistance (dry/wet) (cycles)	25600/12800	25600/12800	cycles
Outsole	**Phylon/Rubber (NBR)**			
	Outsole abrasion resistance (volume loss)	≤ 150	81.0	mm^3
	Outsole slip resistance SRA: heel	≥ 0.28	0.48	friction
	Outsole slip resistance SRA: flat	≥ 0.32	0.45	friction
	Outsole slip resistance SRB: heel	≥ 0.13	N/A	friction
	Outsole slip resistance SRB: flat	≥ 0.18	N/A	friction
	Antistatic value	0.1 - 1000	N/A	MegaOhm
	ESD value	0.1 - 100	N/A	MegaOhm
	Heel energy absorption	≥ 20	34	J

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Carbon footprint:

	Description	Result	Measure unit
CO2 emission			
	Material	1.98	kg
	Packing	0.10	kg
	Manufacturing	1.90	kg
	Transport	0.26	kg
		4.24 kg CO2/pair	

	Description	Result
Recycled content		
	Product	16%
	Packing	98%

CO2 calculation:
Values are rounded to two decimals.
These analyses are performed using our in-house environmental calculators, developed within the Cortina Group. The CO2 values are valid at the time of calculation and may be subject to change.