



**SAFETY  
JOGGER**  
PROFESSIONAL



Light

## MAUD OB

**Sporty and ultra-light sneaker for her**

The MAUD medical shoes are the ultimate in comfort and safety. With SR slip resistance, a removable footbed, 3D mesh, breathable upper, and lightweight design, these shoes are designed to keep you safe and comfortable.

Upper	Mesh
Lining	Mesh
Footbed	SJ foam footbed
Outsole	Phylon/Rubber
Category	OB / SRA, E
Size range	EU 35-42 / UK 3.0-8.0 / US 5.5-10.5 JPN 21.5-26.5 / KOR 230-270
Sample weight	0.264 kg
Norms	EN ISO 20347:2012



FUX



BLK



LGR



NAV




WHT



### 3D mesh

Three-dimensional produced distance mesh to provide increased moisture and temperature management.




### Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.




### SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



### Breathable upper

Increased moisture and temperature management for extended wearer comfort.



### Oxygrip / SJ Grip

Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.



**Solutions for every workplace**

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED  
IN EUROPE

www.safetyjogger.com

**Industries:**

Catering, Cleaning, Food &amp; beverages, Medical

**Environments:**

Dry environment

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
<b>Upper</b>	<b>Mesh</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	1.4	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	15.5	≥ 15
<b>Lining</b>	<b>Mesh</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	28.9	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	231.3	≥ 20
<b>Footbed</b>	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
<b>Outsole</b>	<b>Phylon/Rubber</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	81.0	≤ 150
	Outsole slip resistance SRA: heel	friction	0.48	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.45	≥ 0.32
	Outsole slip resistance SRB: heel	friction	N/A	≥ 0.13
	Outsole slip resistance SRB: flat	friction	N/A	≥ 0.18
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	34	≥ 20

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.