



Medium

## MICKEY COOL 02

MICOOL

**Comfortable full-leather sneaker with iconic Mickey ears**

MICKEY COOL is a must-have for Disney enthusiasts, as it merges certified protection with the iconic ears of Mickey Mouse. Crafted with natural and breathable Nappa leather, a lightweight design and heel energy absorption, this safety shoe offers unrivaled comfort. MICKEY COOL has a slip-resistant rubber outsole and offers ESD protection.


|               |   |
|---------------|---|
| Upper         | Nappa Leather   |
| Lining        | Mesh  |
| Footbed       | SJ foam footbed   |
| Outsole       | Rubber (NBR)  |
| Category      | O2 / ESD, SRC, FO, HRO  |
| Size range    | EU 35-47 / UK 3.0-12.0 / US 3.0-13.0<br>JPN 21.5-31 / KOR 230-310 |
| Sample weight | 0.368 kg  |
| Norms         | ASTM F2892:2018<br>EN ISO 20347:2012                              |




BLK



WHT


**Breathable leather upper**  
Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.




**Electrostatic Discharge (ESD)**  
ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.




**Oxygrip / SJ Grip**  
Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.



**SRC slip resistance**  
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



**Heel energy absorption**  
Heel energy absorption reduces the impact of jumps or running on the body of the wearer.



**Forefoot energy absorption**  
Forefoot energy absorption reduces the impact of jumps or running on the body of the wearer.

**Industries:**

Catering, Cleaning, Food &amp; beverages, Medical, Industry, Uniform

**Environments:**

Dry environment, Extreme slippery surfaces

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

|                | Description                                     | Measure unit          | Result      | EN ISO 20347 |
|----------------|---|-----------------------|-------------|--------------|
| <b>Upper</b>   | <b>Nappa Leather</b>                            |                       |             |              |
|                | Upper: permeability to water vapor              | mg/cm <sup>2</sup> /h | 1.38        | ≥ 0.8        |
|                | Upper: water vapor coefficient                  | mg/cm <sup>2</sup>    | 17          | ≥ 15         |
| <b>Lining</b>  | <b>Mesh</b>                                     |                       |             |              |
|                | Lining: permeability to water vapor             | mg/cm <sup>2</sup> /h | 37.3        | ≥ 2          |
|                | Lining: water vapor coefficient                 | mg/cm <sup>2</sup>    | 299         | ≥ 20         |
| <b>Footbed</b> | <b>SJ foam footbed</b>                          |                       |             |              |
|                | Footbed: abrasion resistance (dry/wet) (cycles) | cycles                | 25600/12800 | 25600/12800  |
| <b>Outsole</b> | <b>Rubber (NBR)</b>                             |                       |             |              |
|                | Outsole abrasion resistance (volume loss)       | mm <sup>3</sup>       | 130         | ≤ 150        |
|                | Outsole slip resistance SRA: heel               | friction              | 0.36        | ≥ 0.28       |
|                | Outsole slip resistance SRA: flat               | friction              | 0.37        | ≥ 0.32       |
|                | Outsole slip resistance SRB: heel               | friction              | 0.18        | ≥ 0.13       |
|                | Outsole slip resistance SRB: flat               | friction              | 0.25        | ≥ 0.18       |
|                | Antistatic value                                | MegaOhm               | N/A         | 0.1 - 1000   |
|                | ESD value                                       | MegaOhm               | 32          | 0.1 - 100    |
|                | Heel energy absorption                          | J                     | 24          | ≥ 20         |

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.