SAFETY JOGGER
PROFESSIONAL



Light

ODILE OB

Work Sandal With Velcro Closure

ODILE safety sandals provide SR slip resistance, ESD protection, and a breathable upper for comfort on dry or slippery floors.

Upper	Action Leather
Lining	Recycled Mesh (100% recycled)
Footbed	N/A
Outsole	Phylon/Rubber (NBR)
Category	OB / SRC, A, E, ESD
Size range	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 JPN 21.5-31 / KOR 230-310
Sample weight	0.260 kg
Norms	ASTM F2892:2018 EN ISO 20347:2012

CO_2 3.82 kg



WHT



BLK




Electrostatic Discharge (ESD)
ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.




SRC slip resistance
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Breathable upper
Increased moisture and temperature management for extended wearer comfort.



Rubber outsole
Rubber outsoles provide versatile functions that make them suitable for many areas of application: excellent cut resistance, heat and cold resistance, high flexibility at cold temperatures, resistance against oil, fuel and many chemicals.



Heel energy absorption
Heel energy absorption reduces the impact of jumps or running on the body of the wearer.

Industries:
Medical

Environments:
Dry environment, Extreme slippery surfaces

Test results:

	Description	EN ISO 20347	Result	Measure unit
Upper	**Action Leather**			
	Upper: permeability to water vapor	≥ 0.8	1.2	mg/cm^2 /h
	Upper: water vapor coefficient	≥ 15	15.2	mg/cm^2
Lining	**Recycled Mesh (100% recycled)**			
	Lining: permeability to water vapor	≥ 2	28.7	mg/cm^2 /h
	Lining: water vapor coefficient	≥ 20	231.3	mg/cm^2
Footbed	**N/A**			
	Footbed: abrasion resistance (dry/wet) (cycles)	25600/12800	25600/12800	cycles
Outsole	**Phylon/Rubber (NBR)**			
	Outsole abrasion resistance (volume loss)	≤ 150	111	mm^3
	Outsole slip resistance SRA: heel	≥ 0.28	0.46	friction
	Outsole slip resistance SRA: flat	≥ 0.32	0.52	friction
	Outsole slip resistance SRB: heel	≥ 0.13	0.14	friction
	Outsole slip resistance SRB: flat	≥ 0.18	0.19	friction
	Antistatic value	0.1 - 1000	N/A	MegaOhm
	ESD value	0.1 - 100	68	MegaOhm
	Heel energy absorption	≥ 20	31	J

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Carbon footprint:

	Description	Result	Measure unit
CO2 emission			
	Material	1.57	kg
	Packing	0.10	kg
	Manufacturing	1.90	kg
	Transport	0.26	kg
		3.82 kg CO2/pair	

	Description	Result
Recycled content		
	Product	5%
	Packing	99%

CO2 calculation:
Values are rounded to two decimals.
These analyses are performed using our in-house environmental calculators, developed within the Cortina Group. The CO2 values are valid at the time of calculation and may be subject to change.