



Comfortable leather sandal

The OLGA sandals are designed for comfort and safety, featuring ESD technology and superior support, and a tight grip. Ideal for medical professionals in dry and slippery environments.

	•
Outsole	Rubber (NBR)
Category	OB / ESD, A, SRC, E
Size range	EU 35-42 / UK 3.0-8.0 / US 5.5-10.5 JPN 21.5-26.5 / KOR 230-270
Sample weight	0.228 kg
Norms	ASTM F2892:2018







EN ISO 20347:2012





















Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Coolmax® lining

Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.



Industries:

Medical

Environments:

Dry environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347		
Outsole	Rubber (NBR)					
	Outsole abrasion resistance (volume loss)	mm³	111	≤ 150		
	Outsole slip resistance SRA: heel	friction	0.46	≥ 0.28		
	Outsole slip resistance SRA: flat	friction	0.52	≥ 0.32		
	Outsole slip resistance SRB: heel	friction	0.14	≥ 0.13		
	Outsole slip resistance SRB: flat	friction	0.19	≥ 0.18		
	Antistatic value	MegaOhm	N/A	0.1 - 1000		
	ESD value	MegaOhm	68	0.1 - 100		
	Heel energy absorption	J	31	≥ 20		

Sample size: 37

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



