

SAFETY JOGGER PROFESSIONAL

Heavy

OXYCLOG OB

Autoclavable Work Clogs

The OXYCLOG clogs are versatile, durable, and comfortable clogs with exceptional slip resistance, ESD, and is washable, autoclavable, and UV sterilizable.

Upper	TPE
Lining	N/A
Footbed	SJ Recycled Foam Footbed (96% recycled)
Outsole	TPE
Category	OB / SRA, A, E, ESD
Size range	EU 35-48 / UK 3.0- / US 5.5- JPN 21.5- / KOR 230-
Sample weight	0.248 kg
Norms	ASTM F2892:2024 EN ISO 20347:2012



RED



EBL BLU EGN FUX



WHT BLK LBL



Autoclavable
Can be sterilized in an autoclave.



Electrostatic Discharge (ESD)
ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



SRA slip resistance
Slip resistance is one of the most important features of safety and occupational footwear. SRA slip resistant soles are tested on a ceramic tile with dilute soap solution.



Washable 90°C
These shoes can be washed in a washing machine at 90°C.



Chemically & UV sterilizeable
This shoe is chemically and UV sterilizeable.



Hygienic waterproof solution
This shoe is made with materials that are waterproof, antibacterial and extremely light & flexible. This makes it a safe, hygienic and comfortable solution for applications in wet environments, such as cleaning or escorting patients into the shower.

Industries:
Medical, Food & beverages, Cleaning

Environments:
Dry environment, Extreme slippery surfaces, Uneven surfaces, Wet environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

Test results:

	Description	EN ISO 20347	Result	Measure unit
Upper	**TPE**			
	Upper: permeability to water vapor	≥ 0.8	N/A	mg/cm^2/h
	Upper: water vapor coefficient	≥ 15	N/A	mg/cm^2
Lining	**N/A**			
	Lining: permeability to water vapor	≥ 2	N/A	mg/cm^2/h
	Lining: water vapor coefficient	≥ 20	N/A	mg/cm^2
Footbed	**SJ Recycled Foam Footbed (96% recycled)**			
	Footbed: abrasion resistance (dry/wet) (cycles)	25600/12800	25600/12800	cycles
Outsole	**TPE**			
	Outsole abrasion resistance (volume loss)	≤ 150	120	mm^3
	Outsole slip resistance SRA: heel	≥ 0.28	0.41	friction
	Outsole slip resistance SRA: flat	≥ 0.32	0.41	friction
	Outsole slip resistance SRB: heel	≥ 0.13	N/A	friction
	Outsole slip resistance SRB: flat	≥ 0.18	N/A	friction
	Antistatic value	0.1 - 1000	90	MegaOhm
	ESD value	0.1 - 100	N/A	MegaOhm
	Heel energy absorption	≥ 20	34	J

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Carbon footprint:

	Description	Result	Measure unit
CO2 emission			
	Material	2.46	kg
	Packing	0.10	kg
	Manufacturing	1.90	kg
	Transport	0.26	kg
		4.72 kg CO2/pair	

	Description	Result
Recycled content		
	Product	10%
	Packing	98%

CO2 calculation:
Values are rounded to two decimals.
These analyses are performed using our in-house environmental calculators, developed within the Cortina Group. The CO2 values are valid at the time of calculation and may be subject to change.