

SAFETY JOGGER

PROFESSIONAL

Heavy

OXYCLOG OB

The clog that meets all your needs

The OXYCLOG clogs are versatile, durable, and comfortable clogs with exceptional slip resistance, ESD, and is washable, autoclavable, and UV sterilizable.

| | |
|---------------|--|
| Upper | TPE |
| Lining | N/A |
| Footbed | SJ foam footbed |
| Outsole | TPE |
| Category | OB / ESD, A, SRA, E |
| Size range | EU 35-48 / UK 3.0- / US 5.5- JPN 21.5- / KOR 230- |
| Sample weight | 0.248 kg |
| Norms | ASTM F2892:2018 EN ISO 20347:2012 |



BLU



BLK

EBL

EGN

FUX



LBL

RED

WHT



Autoclavable
Can be sterilized in an autoclave.



Electrostatic Discharge (ESD)
ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



SRA slip resistance
Slip resistance is one of the most important features of safety and occupational footwear. SRA slip resistant soles are tested on a ceramic tile with dilute soap solution.



Washable 90°C
These shoes can be washed in a washing machine at 90°C.



Chemically & UV sterilizeable
This shoe is chemically and UV sterilizeable.



Hygienic waterproof solution
This shoe is made with materials that are waterproof, antibacterial and extremely light & flexible. This makes it a safe, hygienic and comfortable solution for applications in wet environments, such as cleaning or escorting patients into the shower.

Industries:

Medical, Food & beverages, Cleaning

Environments:

Dry environment, Extreme slippery surfaces, Uneven surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20347 |
|----------------|---|-----------------------|-------------|--------------|
| Upper | TPE | | | |
| | Upper: permeability to water vapor | mg/cm ² /h | N/A | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | N/A | ≥ 15 |
| Lining | N/A | | | |
| | Lining: permeability to water vapor | mg/cm ² /h | N/A | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm ² | N/A | ≥ 20 |
| Footbed | SJ foam footbed | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| Outsole | TPE | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 120 | ≤ 150 |
| | Outsole slip resistance SRA: heel | friction | 0.41 | ≥ 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.41 | ≥ 0.32 |
| | Outsole slip resistance SRB: heel | friction | N/A | ≥ 0.13 |
| | Outsole slip resistance SRB: flat | friction | N/A | ≥ 0.18 |
| | Antistatic value | MegaOhm | 90 | 0.1 - 1000 |
| | ESD value | MegaOhm | N/A | 0.1 - 100 |
| | Heel energy absorption | J | 34 | ≥ 20 |

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.