



Medium

PAOLA 01

Low, leather sneaker for her

PAOLA is a low cut leather sneaker for her that meets the latest fashion trends as well as the strictest safety standards.

Upper	Action Leather
Lining	Mesh
Footbed	SJ foam footbed
Outsole	Rubber
Category	O1 / ESD, SRC
Size range	EU 35-42 / UK 3.0-8.0 / US 5.5-10.5 JPN 21.5-26.5 / KOR 230-270
Sample weight	0.303 kg
Norms	ASTM F2892:2018 EN ISO 20347:2012




NAV



BLK



FUX




Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.




Heel energy absorption

Heel energy absorption reduces the impact of jumps or running on the body of the wearer.



Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.



Oxygrip / SJ Grip

Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.

Industries:

Catering, Cleaning, Food & beverages, Medical

Environments:

Dry environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	Action Leather			
	Upper: permeability to water vapor	mg/cm ² /h	2.5	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	28	≥ 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	55	≥ 2
	Lining: water vapor coefficient	mg/cm ²	390	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	Rubber			
	Outsole abrasion resistance (volume loss)	mm ³	65	≤ 150
	Outsole slip resistance SRA: heel	friction	0.4	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.4	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.17	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.21	≥ 0.18
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	31	0.1 - 100
	Heel energy absorption	J	30	≥ 20

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.