

SAFETY JOGGER

INDUSTRIAL

PRODRY 12PACK 2131X

PRODRY12P

The all-in-one safety gloves with double latex coating

The seamless water repellent PRODRY gloves of Safety Jogger are designed for activities in every environment and for every weather condition. The polyester/nylon liner is provided with a fully latex coating (sky blue colour) and a second roughened latex coating (black colour) on the palm of the hand. Polyester/nylon liner with maximum comfort. Keep

Performance level	2131X
Liner	15 Gauge Recycled Polyester/Rubber(NBR)
Coating	Latex/Latex Sandy
Category	SIF-Silicone Free
Size range	EU 7-12
Sample weight	0.042 kg
Norms	ANSI/ISEA 105:2016 EN ISO 21420:2020 EN 388:2016



EN ISO 21420

EN 388:2016



Industries:

Assembly, Automotive, Chemical, Cleaning, Construction, Industry, Logistics, Mining, Oil & Gas, Tactical

Double layer coating

These gloves have two layers of coating: the first layer offers superior protection, while the second provides excellent grip, even in wet or humid conditions.

Water repellent

Keeps your hands dry by repelling water and moisture.



BLB

Performance level 2131X

EN388:2016	0	1	2	3	4	5
a. Abrasion resistance (cycles)	< 100	100	500	2000	8000	-
b. Cut resistance (Coup test)	< 1.2	1.2	2.5	5.0	10.0	20.0
c. Tear resistance (newton)	< 10	10	25	50	75	-
d. Puncture resistance (newton)	< 20	20	60	100	150	-

EN ISO 13997 (TDM-100 test)	A	B	C	D	E	F
e. Straight blade cut resistance (TDM 100 test)	2	5	10	15	22	30

- a. Abrasion resistance: based on the number of cycles required to rub through the sample glove.
- b. Cut resistance: based on the number of cycles required to cut through the sample at a constant speed with a rotating blade.
- c. Tear resistance: based on the amount of force required to tear the sample.
- d. Puncture resistance: based on the amount of force required to pierce the sample with a standard sized point.
- e. Cut resistance according TDM100 test based on the number of cycles required to cut through the sample at a constant speed with a sliding blade.

