

PROFLEX 12PACK 2131A

PROFLEX12P

Safety work gloves

Safety Jogger PROFLEX work gloves provide high-level protection and comfort in tough industries and environments. Features include durability, comfort, and resistance to wear and tear.

Performance level	2131A
Liner	13 GAUGE POLYESTER
Coating	LATEX
Size range	EU 6-12
Sample weight	0.400 kg
Norms	EN ISO 21420:2020 EN 388:2016



EN ISO 21420

EN 388:2016



Industries:

Assembly, Automotive, Chemical, Cleaning, Construction, Industry, Logistics, Mining, Oil & Gas, Tactical

Extraordinary grip

You'll have a firm hold on objects whether they are dry, wet, or oily, thanks to the exceptional grip these gloves provide.



BLK

Performance level 2131A

EN388:2016	0	1	2	3	4	5
a. Abrasion resistance (cycles)	< 100	100	500	2000	8000	-
b. Cut resistance (factor)	< 1.2	1.2	2.5	5.0	10.0	20.0
c. Tear resistance (newton)	< 10	10	25	50	75	-
d. Puncture resistance (newton)	< 20	20	60	100	150	-

EN ISO 13997 (TDM-100 test)	A	B	C	D	E	F
e. Straight blade cut resistance (newton)	2	5	10	15	22	30

- Abrasion resistance: based on the number of cycles required to rub through the sample glove.
- Cut resistance: based on the number of cycles required to cut through the sample at a constant speed with a rotating blade.
- Tear resistance: based on the amount of force required to tear the sample.
- Puncture resistance: based on the amount of force required to pierce the sample with a standard sized point.
- Cut resistance according TDM100 test based on the number of cycles required to cut through the sample at a constant speed with a sliding blade.