



## PROIMPACT SINGLE 4X42CP

### PROIMPACTS Impact Gloves

Safety Jogger PRO IMPACT gloves deliver advanced impact protection and comfort for assembly, automotive, industry and construction tasks.

Performance level	4X42CP
Liner	13 Gauge/HPPE/Polyamide/Polyester/Glass Fibre/Spandex
Coating	Foam Nitrile
Category	TSF-Touchscreen function, SIF-Silicone Free
Size range	EU 7-12
Sample weight	0.078 kg
Norms	ANSI/ISEA 105:2016 ANSI/ISEA 138-2019 EN ISO 21420:2020 EN 388:2016



EN ISO 21420

EN 388:2016



### Industries:

Automotive, Assembly, Construction, Industry

### Impact resistant

These gloves have extra padding to protect your palms and knuckles from impacts, reducing the risk of injury.

### Excellent cut resistance

These gloves provide excellent protection against cuts, meeting the second-highest level of cut resistance according to the EN 388 standard. They are ideal for tasks with a higher risk of cuts.



514

### Performance level 4X42CP

EN388:2016	0	1	2	3	4	5
a. Abrasion resistance (cycles)	< 100	100	500	2000	8000	-
b. Cut resistance (Coup test)	< 1.2	1.2	2.5	5.0	10.0	20.0
c. Tear resistance (newton)	< 10	10	25	50	75	-
d. Puncture resistance (newton)	< 20	20	60	100	150	-

EN ISO 13997 (TDM-100 test)	A	B	C	D	E	F
e. Straight blade cut resistance (TDM 100 test)	2	5	10	15	22	30

- a. Abrasion resistance: based on the number of cycles required to rub through the sample glove.
- b. Cut resistance: based on the number of cycles required to cut through the sample at a constant speed with a rotating blade.
- c. Tear resistance: based on the amount of force required to tear the sample.
- d. Puncture resistance: based on the amount of force required to pierce the sample with a standard sized point.
- e. Cut resistance according TDM100 test based on the number of cycles required to cut through the sample at a constant speed with a sliding blade.

