SAFETY JOGGER
INDUSTRIAL



Heavy

WINTERBOX ARAS

PROMOARAS

Winterbox including the ARAS safety boot

The Safety Jogger Winter Box offers professionals the ultimate in safety gear with the ARAS S3 boots, durable work gloves, a pair of socks and a warm beanie.

Upper	Nappa Action Leather
Lining	3M Thinsulate
Footbed	SJ Recycled Foam Footbed (96% recycled)
Outsole	PU/PU
Toecap	Composite
Size range	EU 38-48 / UK 5.0-13.0 / US 5.5-13.5 JPN 24-31.5 / KOR 250-315

CO_2 12.45 kg



BLK



Cold insulated (CI)
Cold insulated (CI) safety shoes keep your feet warm. They are worn in cold environments.




Electrostatic Discharge (ESD)
ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



S3
S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



SRC slip resistance
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Metal free
Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



SJ Foam
Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.

Industries:
Automotive, Chemical, Cleaning, Construction, Industry, Mining, Oil & Gas

Environments:
Dry environment, Snowy and icy, Wet environment, Uneven surfaces, Extreme slippery surfaces, Cold environment, Muddy environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

Test results:

	Description		Result	Measure unit
Upper	**Nappa Action Leather**			
	Upper: permeability to water vapor	≥ 0.8	2	mg/cm^2 /h
	Upper: water vapor coefficient	≥ 15	25.5	mg/cm^2
Lining	**3M Thinsulate**			
	Lining: permeability to water vapor	≥ 2	21.6	mg/cm^2 /h
	Lining: water vapor coefficient	≥ 20	173	mg/cm^2
Footbed	**SJ Recycled Foam Footbed (96% recycled)**			
	Footbed: abrasion resistance (dry/wet) (cycles)	25600/12800	25600/12800	cycles
Outsole	**PU/PU**			
	Outsole abrasion resistance (volume loss)	≤ 150	41	mm^3
	Outsole slip resistance SRA: heel	≥ 0.28	0.35	friction
	Outsole slip resistance SRA: flat	≥ 0.32	0.37	friction
	Outsole slip resistance SRB: heel	≥ 0.13	0.13	friction
	Outsole slip resistance SRB: flat	≥ 0.18	0.18	friction
	Antistatic value	0.1 - 1000	N/A	MegaOhm
	ESD value	0.1 - 100	79	MegaOhm
	Heel energy absorption	≥ 20	31	J
Toecap	**Composite**			
	Impact resistance toecap (clearance after impact 100J)	N/A	N/A	mm
	Compression resistance toecap (clearance after compression 10kN)	N/A	N/A	mm
	Impact resistance toecap (clearance after impact 200J)	N/A	16	mm
	Compression resistance toecap (clearance after compression 15kN)	N/A	23	mm

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Carbon footprint:

	Description	Result	Measure unit
CO2 emission			
	Material	10.16	kg
	Packing	0.14	kg
	Manufacturing	1.90	kg
	Transport	0.26	kg
		12.45 kg CO2/pair	

	Description	Result
Recycled content		
	Product	4%
	Packing	99%

CO2 calculation:
Values are rounded to two decimals.
These analyses are performed using our in-house environmental calculators, developed within the Cortina Group. The CO2 values are valid at the time of calculation and may be subject to change.