

Heavy

WINTERBOX NORDIC S3S

PROMONORDI

Winterbox including the NORDIC safety boot

Winterbox including 1 pair of NORDIC safety boots, 1 pair of socks, 1 pair of winter working gloves and a warm Safety Jogger beanie.

Upper	Full Grain Leather
Lining	Teddy
Footbed	Fur
Midsole	Anti-Puncture Textile
Outsole	PU/TPU
Toecap	Composite
Category	S3S / SR, FO, CI
Size range	EU 36-47 / UK 3.5-12.0 / US 4.0-13.0 JPN 22.5-31 / KOR 235-310
Sample weight	0.825 kg
Norms	ASTM F2413:2018 EN ISO 20345:2022+A1:2024

CO_2 5.94 kg



217



Cold insulated (CI)
Cold insulated (CI) safety shoes keep your feet warm. They are worn in cold environments.



Oil & fuel resistant
The outsole is resistant against oil and fuel.



Water resistant Upper (WRU)
Prevents penetration of water if not permanently exposed to high levels.



Breathable leather upper
Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



Composite toecap
Metalfree and lightweight, no thermal or electrical conductivity

Industries:
Automotive, Chemical, Cleaning, Construction, Logistics, Mining, Oil & Gas, Industry

Environments:
Cold environment, Dry environment, Muddy environment, Snowy and icy, Uneven surfaces, Wet environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

Test results:

	Description	EN ISO 20345	Result	Measure unit
Upper	**Full Grain Leather**			
	Upper: permeability to water vapor	≥ 0.8	2.6	mg/cm^2 /h
	Upper: water vapor coefficient	≥ 15	25.8	mg/cm^2
Lining	**Teddy**			
	Lining: permeability to water vapor	≥ 2	34.5	mg/cm^2 /h
	Lining: water vapor coefficient	≥ 20	276.9	mg/cm^2
Footbed	**Fur**			
	Footbed: abrasion resistance (dry/wet) (cycles)	25600/12800	25600/12800	cycles
Outsole	**PU/TPU**			
	Outsole abrasion resistance (volume loss)	≤ 150	67.4	mm^3
	Outsole slip resistance SRA: heel	≥ 0.28	0.38	friction
	Outsole slip resistance SRA: flat	≥ 0.32	0.37	friction
	Outsole slip resistance SRB: heel	≥ 0.13	0.15	friction
	Outsole slip resistance SRB: flat	≥ 0.18	0.19	friction
	Antistatic value	0.1 - 1000	65.7	MegaOhm
	ESD value	0.1 - 100	N/A	MegaOhm
	Heel energy absorption	≥ 20	33	J
Toecap	**Composite**			
	Impact resistance toecap (clearance after impact 100J)	N/A	N/A	mm
	Compression resistance toecap (clearance after compression 10kN)	N/A	N/A	mm
	Impact resistance toecap (clearance after impact 200J)	≥ 14	16.5	mm
	Compression resistance toecap (clearance after compression 15kN)	≥ 14	17.5	mm

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Carbon footprint:

	Description	Result	Measure unit
CO2 emission			
	Material	3.79	kg
	Packing	0.00	kg
	Manufacturing	1.90	kg
	Transport	0.26	kg
		5.94 kg CO2/pair	

	Description	Result
Recycled content		
	Product	0%
	Packing	70%

CO2 calculation:
Values are rounded to two decimals.
These analyses are performed using our in-house environmental calculators, developed within the Cortina Group. The CO2 values are valid at the time of calculation and may be subject to change.