



Medium

## ROMA81 S3

Low-cut safety shoe with zone traction and tripguard

The ROMA81 low-cut safety shoes offer superior protection with oil & fuel resistant outsole, steel toecap, and puncture-resistant midsole. Features heel energy absorption, slip resistance technology, and static spark protection.

Upper	Nappa Action Leather
Lining	Mesh
Footbed	SJ foam footbed
Midsole	Steel
Toecap	Steel
Category	S3 / SRC
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
Sample weight	0.639 kg
Norms	ASTM F2413:2018 EN ISO 20345:2011



BLK



**S3**  
S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.




**Shoes For Crews**  
Shoes For Crews safety and occupational footwear provides enhanced traction, slip resistance when walking on different slippery surfaces and much more.



**Steel toecap**  
Robust metal support to protect the feet of the wearer against falling or rolling objects.



**Steel midsole**  
Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



**Oil & fuel resistant**  
The outsole is resistant against oil and fuel.



**Heel energy absorption**  
Heel energy absorption reduces the impact of jumps or running on the body of the wearer.

**Industries:**

Automotive, Catering, Cleaning, Construction, Food & beverages, Logistics, Industry, Uniform

**Environments:**

Dry environment, Extreme slippery surfaces, Uneven surfaces, Wet environment

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
<b>Upper</b>	<b>Nappa Action Leather</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	2.25	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	25	≥ 15
<b>Lining</b>	<b>Mesh</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	67.6	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	541	≥ 20
<b>Footbed</b>	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
<b>Toecap</b>	<b>Steel</b>			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	16.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	16.5	≥ 14

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.