



# SAFETY JOGGER

PROFESSIONAL



Medium

## ROMAN 01

**Airy and trendy sneaker for him**

The ROMAN low-cut safety shoes provide comfort and safety, featuring ESD technology, removable memory foam insole and SJ Grip rubber outsoles.

Upper	Synthetic Leather
Lining	Mesh
Footbed	Oxy Hybrid
Outsole	Phylon/Rubber (NBR)
Category	O1 / ESD, SRC
Size range	EU 39-47 / UK 6.0-12.0 / US 6.5-13.0 JPN 25-31 / KOR 255-310
Sample weight	0.275 kg
Norms	ASTM F2892:2018 EN ISO 20347:2012



BLK




GRY



### Memory foam

The removable memory foam insole provides extra comfort during stepping and can be exchanged with your own orthopedic sole.



### Oxygrip / SJ Grip

Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.



### Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



### Coolmax® lining

Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.



### Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.

SAFETY  
JOGGER  
WORKS

**Solutions for every workplace**

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED  
IN EUROPE

[www.safetyjogger.com](http://www.safetyjogger.com)

**Industries:**  
Catering, Cleaning, Food & beverages, Medical

**Environments:**  
Dry environment, Extreme slippery surfaces

**Maintenance instructions:**  
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	<b>Synthetic Leather</b>			
	Upper: permeability to water vapor	mg/cm²/h	3.5	≥ 0.8
	Upper: water vapor coefficient	mg/cm²	30	≥ 15
Lining	<b>Mesh</b>			
	Lining: permeability to water vapor	mg/cm²/h	24.1	≥ 2
	Lining: water vapor coefficient	mg/cm²	193	≥ 20
Footbed	<b>Oxy Hybrid</b>			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	<b>Phylon/Rubber (NBR)</b>			
	Outsole abrasion resistance (volume loss)	mm³	121	≤ 150
	Outsole slip resistance SRA: heel	friction	0.45	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.47	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.19	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.21	≥ 0.18
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	25	0.1 - 100
	Heel energy absorption	J	27	≥ 20

Sample size: 41

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED  
IN EUROPE

www.safetyjogger.com