SAFETY JOGGER
PROFESSIONAL



Light

# SUNNY OB

**Women's Fashionable Sneakers**

Stay comfortable and supported with SUNNY sneakers featuring superior grip and posture pain relief for tough work conditions.

| | |
|---|---|
| Upper | Action Leather |
| Lining | Recycled Mesh (100% recycled) |
| Footbed | SJ Recycled Foam Footbed (96% recycled) |
| Outsole | TPR |
| Category | OB / E |
| Size range | EU 35-42 / UK 3.0-8.0 / US 5.5-10.5<br>JPN 21.5-26.5 / KOR 230-270 |
| Sample weight | 0.347 kg |
| Norms | EN ISO 20347:2022(Europe) |

CE · OXYGRIP · NESKRID

$CO_2$ 7.15 kg



FUX



LBL



LGR



LIC




**Coolmax® lining**
Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.

## Industries:
Catering, Cleaning, Food & beverages, Medical

## Environments:
Dry environment

## Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

## Test results:

| | Description | EN ISO 20347 | Result | Measure unit |
|---|---|---|---|---|
| **Upper** | **Action Leather** | | | |
| | Upper: permeability to water vapor | ≥ 0.8 | 1.1 | mg/$cm^2$ /h |
| | Upper: water vapor coefficient | ≥ 15 | 16.8 | mg/$cm^2$ |
| **Lining** | **Recycled Mesh (100% recycled)** | | | |
| | Lining: permeability to water vapor | ≥ 2 | 51.4 | mg/$cm^2$ /h |
| | Lining: water vapor coefficient | ≥ 20 | 412.1 | mg/$cm^2$ |
| **Footbed** | **SJ Recycled Foam Footbed (96% recycled)** | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | 25600/12800 | 25600/12800 | cycles |
| **Outsole** | **TPR** | | | |
| | Outsole abrasion resistance (volume loss) | ≤ 150 | 135 | $mm^3$ |
| | Basic Slip resistance - Ceramic + NaLS - Forward heel slip | ≥ 0.31 | 0.33 | friction |
| | Basic Slip resistance - Ceramic + NaLS - Backward forepart slip | ≥ 0.36 | 0.38 | friction |
| | SR Slip resistance - Ceramic + glycerin - Forward heel slip | ≥ 0.19 | N/A | friction |
| | SR Slip resistance - Ceramic + glycerin - Backward forepart slip | ≥ 0.22 | N/A | friction |
| | Antistatic value | 0.1 - 1000 | N/A | MegaOhm |
| | ESD value | 0.1 - 100 | N/A | MegaOhm |
| | Heel energy absorption | ≥ 20 | 23.0 | J |

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

## Carbon footprint:

| | Description | Result | Measure unit |
|---|---|---|---|
| **CO2 emission** | | | |
| | Material | 4.89 | kg |
| | Packing | 0.10 | kg |
| | Manufacturing | 1.90 | kg |
| | Transport | 0.26 | kg |
| | | **7.15 kg CO2/pair** | |

| | Description | Result |
|---|---|---|
| **Recycled content** | | |
| | Product | 12% |
| | Packing | 99% |

CO2 calculation:
Values are rounded to two decimals.
These analyses are performed using our in-house environmental calculators, developed within the Cortina Group. The CO2 values are valid at the time of calculation and may be subject to change.