SAFETY JOGGER PROFESSIONAL



Light

SUN OB SLP

SUNOBSLP

Extremely comfortable, slip-resistant and ESD-compliant work sandal

The perfect companion to brighten up your workday. SUN OB has an open design that is extra breathable and comfortable, making both sweaty and sore feet a thing of the past. This slip-on shoe offers ESD protection and has a slip-resistant outsole that prevents slips, trips and falls. Made with lightweight and vegan materials.

Upper	Synthetic Leather
Lining	N/A
Footbed	SJ Recycled Foam Footbed (96% recycled)
Outsole	PU
Category	OB / SRC
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
Sample weight	0.199 kg
Norms	ASTM F3445:2021 EN ISO 20347:2012


CO_2 4.83 kg



WHT



BLK



Breathable upper
Increased moisture and temperature management for extended wearer comfort.



SRC slip resistance
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Removable insole
Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.



Vegan
Uses or contains no animal products.

Industries:
Cleaning, Medical, Food & beverages, Assembly

Environments:
Dry environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

Test results:

	Description	EN ISO 20347	Result	Measure unit
Upper	**Synthetic Leather**			
	Upper: permeability to water vapor	≥ 0.8	1.92	mg/cm^2 /h
	Upper: water vapor coefficient	≥ 15	18	mg/cm^2
Lining	**N/A**			
	Lining: permeability to water vapor	≥ 2	N/A	mg/cm^2 /h
	Lining: water vapor coefficient	≥ 20	N/A	mg/cm^2
Footbed	**SJ Recycled Foam Footbed (96% recycled)**			
	Footbed: abrasion resistance (dry/wet) (cycles)	25600/12800	25600/12800	cycles
Outsole	**PU**			
	Outsole abrasion resistance (volume loss)	≤ 150	140	mm^3
	Outsole slip resistance SRA: heel	≥ 0.28	0.42	friction
	Outsole slip resistance SRA: flat	≥ 0.32	0.39	friction
	Outsole slip resistance SRB: heel	≥ 0.13	0.16	friction
	Outsole slip resistance SRB: flat	≥ 0.18	0.19	friction
	Antistatic value	0.1 - 1000	N/A	MegaOhm
	ESD value	0.1 - 100	N/A	MegaOhm
	Heel energy absorption	≥ 20	32	J

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Carbon footprint:

	Description	Result	Measure unit
CO2 emission			
	Material	2.58	kg
	Packing	0.10	kg
	Manufacturing	1.90	kg
	Transport	0.26	kg
		4.83 kg CO2/pair	

	Description	Result
Recycled content		
	Product	15%
	Packing	99%

CO2 calculation:
Values are rounded to two decimals.
These analyses are performed using our in-house environmental calculators, developed within the Cortina Group. The CO2 values are valid at the time of calculation and may be subject to change.