



Medium

## TACTIC OB

### Mid-cut allround tactical boot

High-cut allround tactical leather boot made for tactical purposes. With it's 562 grams it's an extreme lightweight tactical boot.

Upper	Nappa Action Leather, Textile
Lining	Mesh
Footbed	SJ foam footbed
Outsole	Rubber (NBR)
Category	OB / SRA, FO, HRO
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
Sample weight	0.632 kg
Norms	ASTM F3445:2021 EN ISO 20347:2012



BLK




#### SRA slip resistance

Slip resistance is one of the most important features of safety and occupational footwear. SRA slip resistant soles are tested on a ceramic tile with dilute soap solution.



#### Heat resistant outsole (HRO)

The outsole resists high temperatures up to 300°C.



#### Oil & fuel resistant

The outsole is resistant against oil and fuel.



#### Breathable leather upper

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.

Industries:

Tactical, Uniform

Environments:

Muddy environment, Uneven surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	<b>Nappa Action Leather, Textile</b>			
	Upper: permeability to water vapor	mg/cm²/h	4.5	≥ 0.8
	Upper: water vapor coefficient	mg/cm²	35	≥ 15
Lining	<b>Mesh</b>			
	Lining: permeability to water vapor	mg/cm²/h	45	≥ 2
	Lining: water vapor coefficient	mg/cm²	350	≥ 20
Footbed	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	<b>Rubber (NBR)</b>			
	Outsole abrasion resistance (volume loss)	mm³	85	≤ 150
	Outsole slip resistance SRA: heel	friction	0.28	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.32	≥ 0.32
	Outsole slip resistance SRB: heel	friction	N/A	≥ 0.13
	Outsole slip resistance SRB: flat	friction	N/A	≥ 0.18
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	N/A	≥ 20

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED  
IN EUROPE

www.safetyjogger.com