

Light

TURBO S3

Fashionable low-cut safety shoe for active professionals

Safety Jogger's TURBO safety shoes offer superior grip, heat resistance, and antistatic properties. These shoes keep your feet dry, cool, and fresh.

Upper	Nubuck Action Leather
Lining	3D-Mesh
Footbed	SJ foam footbed
Midsole	Anti-puncture Textile
Outsole	PU/Rubber (NBR)
Toecap	Composite
Category	S3 / SRC, HRO
Size range	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 JPN 21.5-31 / KOR 230-310
Sample weight	0.632 kg
Norms	ASTM F2413:2018 EN ISO 20345:2011



094



S3

S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Heat resistant outsole (HRO)

The outsole resists high temperatures up to 300°C.



Antistatic

Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm



Composite toecap

Metalfree and lightweight, no thermal or electrical conductivity



SJ Flex

Metalfree puncture resistant material, which is lighter and more flexible than steel. The material is not thermal conductive. Covers 100% of the surface of the last bottom.

Industries:

Automotive, Cleaning, Construction, Logistics, Industry

Environments:

Dry environment, Warm surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Nubuck Action Leather			
	Upper: permeability to water vapor	mg/cm²/h	3.9	≥ 0.8
	Upper: water vapor coefficient	mg/cm²	38.4	≥ 15
Lining	3D-Mesh			
	Lining: permeability to water vapor	mg/cm²/h	50.8	≥ 2
	Lining: water vapor coefficient	mg/cm²	406.9	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	PU/Rubber (NBR)			
	Outsole abrasion resistance (volume loss)	mm³	40	≤ 150
	Outsole slip resistance SRA: heel	friction	0.53	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.50	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.14	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.18	≥ 0.18
	Antistatic value	MegaOhm	0.32	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	30	≥ 20
Toecap	Composite			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	17.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	21.5	≥ 14

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com