

Medium

X0600 S3


Safety shoe designed for the food industry

The Safety Jogger X0600 is a low-cut safety shoe ideal for high-humidity industries. It provides superior protection and comfort with water and oil resistance, steel toecap, and midsole. Enjoy pain relief, cool dry feet, and reliable grip.

Upper	Nappa Action Leather
Lining	Cambrella
Footbed	SJ foam footbed
Midsole	Steel
Outsole	PU/PU
Toecap	Steel
Category	S3 / SRC
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
Sample weight	0.585 kg
Norms	ASTM F2413:2018 EN ISO 20345:2011



BLK



Oil & fuel resistant

The outsole is resistant against oil and fuel.



Steel midsole

Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



Water resistant Upper (WRU)

Prevents penetration of water if not permanently exposed to high levels.



S3

S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Steel toecap

Robust metal support to protect the feet of the wearer against falling or rolling objects.

Industries:
Automotive, Catering, Cleaning, Construction, Food & beverages, Logistics, Industry

Environments:
Dry environment, Uneven surfaces, Wet environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Nappa Action Leather			
	Upper: permeability to water vapor	mg/cm²/h	1.0	≥ 0.8
	Upper: water vapor coefficient	mg/cm²	18.2	≥ 15
Lining	Cambrella			
	Lining: permeability to water vapor	mg/cm²/h	95.9	≥ 2
	Lining: water vapor coefficient	mg/cm²	480	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	PU/PU			
	Outsole abrasion resistance (volume loss)	mm³	81.9	≤ 150
	Outsole slip resistance SRA: heel	friction	0.35	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.35	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.14	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.18	≥ 0.18
	Antistatic value	MegaOhm	26.2	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	28	≥ 20
Toecap	Steel			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	15.0	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	16.0	≥ 14

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com